STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

								Well		
Орегатог	MERIDIAN OIL INC.				SAN JUAN 27-5 UNIT			No.	86 <u>M</u>	
Location			0781	_	OFIL			DIO ADDI		
of Well:	Unit J Sect 9 Twp. 27N NAME OF RESERVOIR OR POOL				Rge. 05W		County		RIO ARRIBA	
	NAME OF	TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art. Lift)		PROD. MEDIUM (Tbg. or Csg.)				
I lanca				+'	On or Gas)	(Fig	w of Aft. Lift)	(Ibg. c	r Csg.)	
Upper	MESAVERDE				GAS		FLOW	1	BG	
Completion Lower	WIEGAVERDE			 	uno		11011	'		
Completion	DAKOTA				GAS		FLOW	Т Т	BG	
Completion	DANGTA	PRI	E-FLOW SHUT	-IN PRE		<u> </u>		<u> </u>		
Upper	Hour, date shut-in	Length of time shut-		SI press			Stabilized? (Ye	s or No)		
Completion	6-4-95	-	AYS	1.	335					
Lower										
Completion	6-4-95	3 D	AYS		1010	_				
			FLOW TEST	NO. 1						
Commenced a	at (hour.date)* 6-	7-95			Zone producing	(Upper o	r Lower)	LOWER		
ПМЕ	LAPSED TIME	PRI	SSURE	SURE						
(hour,date)	SINCE*	Upper Completion	Lower Comp	Lower Completion		ļ	REMAR	KS		
		222		7						
5-Jun	 	323	88	/		-				
6-Jun		331	96	4						
7-Jun		335	101	0						
7 00.17									· ·	
8-Jun		339	35	i9						
9-Jun		341	35	i8	ļ	<u> </u>				
Production	rate during test	·.				•				
Oil:	BOPD based o	n Bb	ls. in	Hours	·	_Grav.		GOR		
	-									
Gas:		MCFPD; Tested	thru (Orifice or	Meter):						
		MI	D-TEST SHUT	-IN PRE	SSURE DATA					
Upper	Hour, date shut-in	Length of time shut	-in	SI pres. psig			Stabilized? (Yes or No)			
Completion	ļ									
Lower	Hour, date shut-in	Length of time shut	-in	SI pres	s. psig		Stabilized? (Y	es or No)		
Completion	<u> </u>						<u> </u>			

(Continue on reverse side)

FLOW TEST NO 2

Commenced :	at (hour.date)**			Zone producing (Upp	per or Lower):		
ПМЕ	LAPSED TIME	PR	PRESSURE.				
hour,date)	SINCE**	Upper Completion	Lower Completion	ТЕМР.	REMARKS		
					1		
				-			
	<u> </u>						
		 					
			<u></u>				
Production	rate during test						
0.1							
Dil:					Grav GOR		
Gas:		MCFPD; Te	sted thru (Orifice or	Meter):			
lemarks:							
homber one	aish, ali a ali a i ak	-1 to 1 . 1	1				
neredy cer	my man me miorina	nion nerein containe	is true and complet	e to the best of my ki	nowledge.		
	graved Johnny Relieven 10				Maridian Oil Inc		
Annroyed	ahn	m Relience	\sim $_{\rm id}$	0	Maridian Oil Inc		
Approved	John	ny Roliense	~ 19	Operator	Meridian Oil Inc.		
	1 1		1 1	- ·			
	1 1	ny Roliense Deivision 1995	1 1	Operator By	Meridian Oil Inc. Tanya Atcitty		
New Mex	1 1		1 1	Ву	Tanya Atcitty		
New Mex	tico Oil Conservation	Je ^{ivisio} 9 1995		- ·			
Approved New Mex By Title	tico Oil Conservation			Ву	Tanya Atcitty		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A nactor leakage test small be commenced on each multiply completed well within seven days after except that the previously produced zone shall remain shut-in while the zone which actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be connected on all multiple completions within seven days following recompletion and/or chemical or frac-ture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify he Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The nacker leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization, both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than sever days,
- 4. For flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gus well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall he three hours
- 5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1

- was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time untervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checared at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gaz zone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division of Northwest New Mexico Packer Leakage Test form Revised 10/01/78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).