

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1740'S, 1660'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

☐ ☒ ☐ ☐ ☐ ☐ ☐

RECEIVED

SEP 22 1982

NOTE: Report results of multiple completion or zone change on Form 9-30.1 1002

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-11-82 PBSD 6265'. Tested casing to 3500#, OK. Perf'd 5850', 5854', 5859', 5864', 5874', 5890', 5896', 5917', 5922', 5932', 5936' with 1 spz. Fraced with 57,000# 20/40 sand and 124,000 gal. treated water. Flushed with 7900 gallons water.

Perf'd 5392', 5396', 5428', 5439', 5445', 5452', 5472',
5488', 5501', 5580', 5585', 5590', 5596', 5646', 5755',
5761', 5771', 5776', 5788', 5806' with 1 spz. Fraced
with 35,000# 20/40 sand and 75,600 gallons treated water.
Flushed with 7600 gallons water.

Perf'd 4642", 4646", 4650", 4670", 4684", 4688", 4692' w/1
spz. Fraced w/24000# 20/40 sand and 42,740 gal. treated wat

Subsurface Safety Valve: Manu. and Type Flushed w/7100 gal. water. Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Guedes TITLE Drilling Clerk DATE September 21, 1982

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

SEP 23 1982

FARMINGTON, NICT