Form 3160-5 (November 1983) (Formerly 9-331)	UNITED STATES  SUBMIT IN TRIPLICATE  Other Instructions on re-  BUREAU OF LAND MANAGEMENT	Form approved. Budget Bureau No. 1004-013 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO SF 080671A
(Do not use this fo	ORY NOTICES AND REPORTS ON WELLS  orm for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAM
OIL GAB WELL 2. NAME OF OPERATOR	Х отнев	7. UNIT AGREEMENT NAME San Juan 27-4 Unit
· <del>-</del>	El Paso Natural Gas Company	8. FARM OR LEASE NAME San Juan 27-4 Unit 9. WELL NO.
	Post Office Box 4289, Farmington, NM 87499  port location clearly and in accordance with any State requirements.  1515'S, 910'E  AUG 08 1985	33 10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde 11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 11, T-27-N, R-4
14. PERMIT NO.	15. BLEVATIONS (Show whether DF, RT, GR, etc.) 6822 GL	N.M.P.M.  12. COUNTY OF PARISH 13. STATE  Rio Arriba NM
16. Not Test water shut-off	PEU OR ALTER CARVO	INT REPORT OF:
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	MULTIPLE COMPLETE  ABANDON*  CHANGE PLANS  (Other)  (NOTE: Report results of	ALTERING CABING ABANDONMENT*  f multiple completion on Welicion Report and Log form.)
7-24-85	Clean out to 6314'. Pressure test to 35 6070', 6074', 6128', 6133', 6154', 6165 6255', 6288' w/l spz. Frac'd with 19,00 41,160 gallons treated water. Flushed v  Perf'd second stage 5910', 5914', 5918', 5932', 5936', 5940', 5944', 5972', 5976' 5988', 5998', 6006', 6010', 6014', 6018' Frac'd with 106,000# 20/40 sand and 128,	deluding estimated date of starting any depths for all markers and zones perti-  500#, ok. Perf'd ', 6218', 6226',  00# 20/40 sand and with 8,190 gallons.  5921', 5929', ', 5980', 5984', ', 6022' w/l spz.
7-27-85	water. Flushed with 8,020 gallons.  Set bridge plug at 4016'. Perf'd one so 3350'. Squeeze cemented Ojo Alamo with with 2% calcium chloride (177 cu.ft.).	queeze hole at 150 sks. Class "B"
7-28-85	Clean out to below squeeze. Tested casi Set packer at 3190'. Squeeze cemented w "B" with 2% calcium chloride (88 cu.ft.)	ith 75 sks. Class
7-29-85	Clean out squeeze cement, pressure teste psi, held ok. Now cleaning out to PBTD	ed casing to 1500 with gas.

that the foregoing is true and correct Drilling 8-7-85 TITLE . (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:

OIL CON. DIV.

\*See Instructions on Reverse Side DIST. 3

FARM

1985

FARMINGTON RESUUNCE AREA