Form 3160-5

REPAIR WELL

(Other)

رنيه

## UNITED STATES

CHANGE PLANS

SUBMIT IN TRIPLICATE

Form approved. Budget Bureau No. 1004 0125

	ires Augus			0133
EASE	DESIGNATIO	NAND	ACRIAL	NO

(Formerly 9–331)	DEPARTMENT OF THE INTE BUREAU OF LAND MANAGEMI		5. LEASE DESIGNATION AND SERIAL NO. SF 079391	
(Do not use the	INDRY NOTICES AND REPORTS this form for proposals to drill or to deepen or pluse "APPLICATION FOR PERMIT—" for suc		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
OIL GAB WELL WELL	OTHER		7. UNIT AGREEMENT NAME San Juan 27-5 Unit	
2. NAME OF OPERATOR	El Paso Natural Gas Comp	pany	8. FARM OR LEASE NAME San Juan 27-5 Unit	
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499			9. WELL NO. 126E	
4. LOCATION OF WELL See also space 17 t At surface	(Report location clearly and in accordance with a celegration 1510'W	10. FIELD AND POOL, OR WILDCAT Basin Dakota  11. SEC., T., E., M., OR BLK. AND Sec. T., T. Z., M., OR DAK. AND NMPM		
	BUREA 국소 <b>PM</b> I			
14. PERMIT NO.	15. ELEVATIONS (Show whether		12. COUNTY OF PARISH 13. STATE RIO Arriba NM	
16.	Check Appropriate Box To Indicate	Nature of Notice, Report, or C	Other Data	
NOTICE OF INTENTION TO:			ENT REPORT OF:	
TEST WATER SHUT FRACTURE TREAT SHOOT OR ACIDIZE	PCLL OR ALTER CASING MULTIPLE COMPLETE ABANDON®	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL  ALTERING CASING  Thning Casing	

(Nors: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

TD 3636'. Ran 86 jts. 7", 20.0#, K-55 intermediate casing, 7-18-85 3631' set @ 3643'. Cemented with 100 sks. Class"B" with 6% gel and 2% calcium chloride, 1/2 cu.ft. Perlite (238 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours, held 1200#/30 min. Top of cement @ 2100'.

TD 7809'. Ran 193 jts. 4 1/2", 11.6# & 10.5#, K-55 casing, 7797' set @ 7809'. Float collar @ 7796'. Cemented with 255 7-22-85 sks. Class "B" with 2% D-79, 0.3% D-13, and 2# J51/sk., followed by 100 sks. Class "B" with 0.5% D-65, 0.2 gal/sk D-108 and 0.3% D-13 (total 643 cu.ft.) WOC 18 hours. Top of cement @ 3000'.



		OIL CON. DIV.		
8. I hereby certify that the foregoing is true and correct signed lager back	Drilling Clerk	DIST. 3 7-26-85		
(This space for Federal or State office use)  APPROVED BY	TITLE	ACCEPTED FOR RECORD		
CONDITIONS OF APPROVAL, IF ANY:	IF ANI:		AMG 63 1985	
*Sc	ee Instructions on Reverse Side	FARMINGTON NE	OU. OL MREA	