STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

> This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVI

MAY 2000
MAY

30-039-23823

API#

Page I Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well SAN JUAN 27-5 UNIT No. 69M BURLINGTON RESOURCES OIL & GAS CO. Lease Operator Location **RIO ARRIBA** 005W County Twp. 027N Rge. of Well: 07 PROD. MEDIUM TYPE OF PROD METHOD OF PROD. NAME OF RESERVOIR OR POOL (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper Flow Tubing Gas **MESAVERDE** Completion Lower Tubing Flow DAKOTA Gas Completion PRE-FLOW SHUT-IN PRESSURE DATA SI press. psig Stabilized? (Yes or No) Length of time shut-in Upper Hour, date shut-in Completion 05/04/2000 144 Hours 230 Lower Completion 420 05/04/2000 96 Hours FLOW TEST NO. 1 LOWER 05/08/2000 Zone producing (Upper or Lower) Commenced at (hour date)* PROD. ZONE PRESSURE TIME LAPSED TIME TEMP REMARKS SINCE* Upper Completion Lower Completion (hour,date) turned on dk 230 294 5/09/200 120 Hours 232 187 5/10/200 144 Hours Production rate during test BOPD based on Bbls. in Hours. MCFPD; Tested thru (Orifice or Meter): Gas: MID-TEST SHUT-IN PRESSURE DATA Stabilized? (Yes or No) SI press. psig Upper Hour, date shut-in Length of time shut-in Completion Stabilized? (Yes or No) SI press. psig Hour, date shut-in Length of time shut-in Lower Completion (Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, d	ate)**		Zone producing (Upper or	one producing (Upper or Lower):		
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	DEMARKS	
		Upper Completion	Lower Completio	n TEMP.	REMARKS	
			· · · · · · · · · · · · · · · · · · ·			
	,	,				
	 					
ı						
						
Production rate du	ring test					
Oil:	ВО	PD based on	Bbls. in	Hours	Grav GOR	
Gas:		МСБЫ	D: Tested thru (O	rifice or Meter):		
I hereby certify tha	t the information her	ein contained is true	and complete to	the best of my knowled		
increasy correspond				the best of my knowled	gc.	
Approved	MAY 18	2000 19	·	Operator Burling	ton Resources	
New Mexico O	il Conservation Divis			01	0.	
	ORIGINAL SIGNED	BY CHARLIE T. PE	RAN	By Mores	May	
D _V				Title Operations Associate		
Title GAS INSPECTOR, DIST.				Date Tuesday, May 16, 2000		
		MODERNIEGENENA	EWIGO DA GUEDA			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- as desired, or may be requested on wells which have previously shown questionable test data.

 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).