

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other	5. Lease Designation and Serial No.
2. Name of Operator AMERICAN HUNTER EXPLORATION LTD.	6. If Indian, Allocated or Tribe Name JICARILLA APACHE
3. Address and Telephone No. 410 - 17th STREET; SUITE 1220; DENVER, COLORADO 80202	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2000' FSL & 500' FEL (NESE) SECTION 8 - T27N-R1E	8. Well Name and No. JICARILLA 8I-1
	9. API Well No.
	10. Field and Pool, or Exploratory Area WILDCAT
	11. County or Parish, State RIO ARRIBA, NEW MEXICO

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other NOTICE OF SPUD	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Reference well was spud @ 13:00 hours on 08/31/91. A 14-3/4" surface hole was drilled to a depth of 336'. Surface casing (10-3/4", 40.5#, J55, ST&C) was set @ 336'KB and cemented to surface with 310sx Class 'G' with 2% CaCl₂, 1/4#/sx Cellophane flakes. Lost circulation with no cement returns to surface. A cement job was done from surface with 40 sx Class 'G', 2% CaCl₂ cement stayed at surface. WOC for 5½ hours. Nipple up and pressure test BOP.

~~CONFIDENTIAL~~

ACCEPTED FOR RECORD

MAR 20 1992

FARMINGTON RESOURCE AREA

BY

14. I hereby certify that the foregoing is true and correct.		
Signed <u>B. Thistle</u>	Title <u>Drilling Technologist</u>	Date <u>03/03/92</u>
(This space Federal or State office use)		
Approved by _____	Title _____	Date _____
Conditions of approval, if any:		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side
OPERATOR

RECEIVED
BLM
92 MAR -5 AM 10:43
FARMINGTON RESOURCE AREA