Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

5. Lease Designation and Serial No. 701-90-0001 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. JICARILLA APACHE Use "APPLICATION FOR PERMIT—" for such proposals CONFIDENTIA 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE n/a 1. Type of Well Oil Well 8. Well Name and No. Other ABANDONED Name of Operator JICARILLA 8I-1 AMERICAN HUNTER EXPLORATION LTD. 9. API Well No. 3. Address and Telephone No. 30-039-25093 410 - 17th STREET; SUITE 1220; DENVER, DOLORADO 80202 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) WILDCAT 11. County or Parish, State 2000' FSL & 500' FEL (NESE) RIO ARRIBA COUNTY, SECTION 8, T27N-R1E NEW MEXICO CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Inten: Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Altering Casing Final Abandonment Notice Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completee. Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Set bridge plug @ 1958' KB. Pressure test BP & casing to 1000 psi for 15 mins. held O.K. RIH with open ended tubing and displace hole to 9"/gal mud with 50 VIS. Spot @ 330' cement plug from 1955' to 1625' KB using 76 sacks Class "G" neat cement. 4. Spot @ 100' cement plug from 386' to 286' KB using 23 sacks Class "G" neat cement. Spot surface cement plug from 56' to surface using 12 sacks Class "G" cement. Cut off casing 4' below ground level and weld on 1/4" steel plate. Weld 4" x 8' pipe to plate for ID monument. Operation completed July 23 1992. Restore lease. Approved as in plugging of the well in a Liability under bend is winkled wall surface restoration is completed. 14. I hereby certify that the foregoing is true and correct Tide _Completion_Superintendent (This space for Federal or State office use) Title

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any Alse factoring or fraudulent statements or representations as to any matter within its jurisdiction.

K :

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993