## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## **OIL CONSERVATION DIVISION**

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator <u>UN</u>	NION OIL COMPA			RINCON UNIT		Well No. <u>#126M</u>	
cation Well: Unit	P Sec. <u>27</u>	DBA UI <b>Twp</b> . 27N	NOCAL Rge	6W	County _	RIO ARRIBA	
	NAME OF RESERV		TYPE OF P	ROD. ME	THOD OF PROD. Flow or Art. LHQ	PROD. MEDIUM (Tbg. or Cog.)	
Ipper npletion	MESA VERDE	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	GAS		FLOW	ANNULUS	
ower npietion	DAKOTA		GAS		FLOW	TUBING	
		PRE-FL	OW SHUT-IN P	RESSURE DATA			
pper	our, date shut-in Length of time shut-			SI press, paig	<b>!</b>	Stabilized? (Yes or No)	
Hour, o	ARCH 16, 1993	8: 45AM Length of time sh	7 DAYS	81 press. psig	. 860 Steblii	YES	
npletion MA	ARCH 16, 1993	8:45AM	7 DAYS	TBG	. 1075	NO	
			FLOW TEST	NO. 1			
menced at the	ur, date) # MARCI	1 23, 1993	9:30AM	Zone producing (Upp	er er Lowerk I	LOWER	
TIME LAPSED TIME		PRES	PRESSURE			REMARKS	
(hour, date)	SINCE*	Upper Completion	Lewer Completion	TEMP.		KEMANNA	
3/24/93	24 HRS.	CSG. 860	TBG. 780	73°	Q = 567	MCF/D	
3/25/93	48 HRS.	CSG. 860	TBG. 400	64°	Q = 567	MCF/D	
	te during test	PD based on	Bbls. in	Hours.	Grav.	GOR	
s:		MCI	PD; Tested thru	(Orifice or Meter)	):		
3:				RESSURE DATA			
s:		MID-T	EST SHUT-IN P	dasold Ditin			
	date shul-in	MID-T		Si press. peig	Stabil	ized? (Yes or No)	

REGEIVE D

(Continue on reverse side)

OIL CON. DIV

FLOW TEST NO. 2

Commenced at (hour, da	(10) 구 주			Zone producing (Upper or Lower):		
TIME	LAPSED TIME	[————	SURE	PROD. ZONE	REMARKS	
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP,	nemana	
			<del> </del>	<b></b>		
· · · · · · · · · · · · · · · · · · ·						
	<del> </del>					
	ļ					
				·		
D 1		<u> </u>		'•		
Production rate d	uring test					
Oil:	BOP	D based on	Bbls. in	Hours.	Grav GOR	
					· · · · · · · · · · · · · · · · · · ·	
				(Office of Meter)		
Remarks:	<del></del>					
I hereby certify th	at the information	on herein containe	ed is true and con	mplete to the best	of my knowledge.	
Approved	MAN I W		19 0	Decator UNION	OIL COMPANY OF CALIFORNIA DBA	IINOCA
Approved			/	•		
Cognid Speed by MARIES GHOLSON			В	y	dy Riese	
			т	ide GENERA	AL CLERK	
Tide <u>Potatio</u>	10 m 日本 1795 25	TON, DIET, 358	D	ate MARCH	29, 1993	

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone terus: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).