- STATE OF NEW MEXICO

- ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

Well

This form is not to be used for reporting packer leakage tests in Southeastern New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator		ION O	IL OF CALIFOR	(NIA/dba	UNOCAL	Lease RIN	ICON UNIT	1	No. 108E
Location									
of Well:	Unit O Sec. 19 Twp. 27N			Rge06V	V	County	RIO ARRIBA		
			NAME OF RESE	RVOIR OR	POOL	TYPE OF P (Oil or Ga		METHOD OF PROD (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)
Upper Completion				GAS	FLOW		TUBING		
Lower Completion BASIN DAKOTA				GAS	FLOW		TUBING		
					PRF_FT	OW SHUT-IN PR	ECCIDE DATA		-
Upper		ate shut-	in		Length of time shu		SI press. psig CSG 290	s	Stabilized? (Yes or No)
Completion		24/97		ļ	5 DAYS		TBG -		10
Lower Completion	Hour, da 9: a		ⁱⁿ 7/24/97		Length of time shu	t-in	SI press. psig TBG 480		tabilized? (Yes or No)
						FLOW TEST N	D. 1	-	
Commenced	at (hour,	date)*	3:45 p.m. 07	/29/97			Zone producing (Upper	or Lower)* Lower	
	ME		LAPSED TIME SINCE*		PRES		PROD. ZONE		REMARKS
9:30 а.п	, date)	+	SINCE		pper Completion	Lower Completion	TEMP.		
07/30/97			24 hrs		BG 200	TBG 170	59 ° -	Q = 259 mg	:f
8:40 a.m 07/31/97			48 hrs	- 1	SG 280 BG 200	TBG 160	62°		
01701101		T	40 1113			180 100	02	Q = 329 m	
		Ť						DEG	EIVEN
								AUG 1	3 1997
	_								
roduction r	rate duri	ng test							क जाता
rit:			ВОІ	D based	on	Bbls. in	Hours.	Grav.	GOR
as:					MCFPD; Test	ed thru (Orifice or Me	eter):		
				M	IID-TEST SH	UT-IN PRESSUR	E DATA		
Hour, date shut-in Upper Con etion				Length of time shut-		SI press. psig CSG TBG	Sta	abilized? (Yes or No)	
Lower Hour, date shut-in			İ	Length of time shut-i	in .	SI press. psig	Sta	bilized? (Yes or No)	

(Continue on reverse side)

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

			FLOW TEST NO). I		
Commenced at (hour, date	e)*			Zone producing (Upper of	or Lower)* UPPER	
TIME	LAPSED TIME	PRES		PROD. ZONE	REMARKS	.5.,
(hour, date)	SINCE*	Upper Completion	Lower Completion	TEMP.		
		CSG				 -
		TBG	TBG			
		CSG				
		TBG	TBG			
		CSG				
		TBG	TBG			
					··.	
	1	<u> </u>				
i		•	!!	<u> </u>		
	ŀ	ĺ				
	1					
Production rate during	g test					
Oil:	BOPD b	pased on	Bbls. in	Hours.	Grav.	GOR
Gas:	e de la companya de	MCFPD; Test	ed thru (Orifice or Me	eter):		
Remarks:				·		
Approved	AUG 18 onservation Division Phring & Deputy Oil &	19 97 19	Ope Ope	UNION OIL Mike Tabet	OF CALIFORNIA/dba UNOCAL alexamore	
Fitle			Date	e August 15th.	1997	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No.1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No.1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No.1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours test: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as a required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10 - 01 - 78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

- STATE OF NEW MEXICO

- ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeastern New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator UNIO	N OIL OF CALIFORNIA	ba UNOCAL	Lease	RINCON UNIT			Well No. 1	08E
Location of Well: Unit	O Sec. 19 Tv	vp. 27N	Rge	06W		Cou	nty RIO AF	RIBA
<u> </u>	NAME OF RESERVOIR	OR POOL	TYPE	OF PROD. or Gas)		METHOD OF I	PROD.	PROD. MEDIUM (Tbg. or Csg.)
Upper Completion OTER	O CHACRA		GAS		FLOW			TUBING
i I	I DAKOTA		GAS	•	FLOW			TUBING
		PRE-FLO	W SHUT-IN	PRESSURE	DATA	- · · · · ·		
Hour, date s	n.	Length of time shut-	in	SI press. CSG	210		Stabilized? (res or No)
Completion 07/24/		5 DAYS		TBG	215		YES	
,	07/24/97	Length of time shut-i	ın	SI press. TBG	320		Stabilized? (1 YES	(es or No)
]	FLOW TEST	Γ NO. 1				
Commenced at (hour, date	e)* 2:45 p.m. 07/29/97			Zone pro	ducing (Upper	or Lower)* L(ower	
TIME (hour, date)	LAPSED TIME SINCE*	PRESSI Upper Completion	URE Lower Comple), ZONE MP.		REMAR	RKS
11:20 a.m. 07/30/97	24 hrs	CSG 220 TBG 220	TBG 170	0 -		Q = 0		
9:15 a.m.	24100	CSG 220	100 170	- 		Q - 0		
07/31/97	48 hrs	TBG 220	TBG 160	68 °		Q = 88 r	ncf	
:		·						
			-				2 G U W	EN
!						DIE (ラGII V	
					72.	_UV AUE	<u>1 3 199</u>	7
		ſ					<u>ලලැබ</u> .	DUM
Production rate during	test						DIT. 3	
Oil:	BOPD bas	sed on	Bbls. in	n	Hours.	Gr	av	GOR '
Gas:		MCFPD; Tested	d thru (Orifice o	or Meter):			- <u></u>	
<u>.</u>		MID-TEST SHU	T-IN PRESS	SURE DATA				
Hour, date sh Upper Completion	ut-in į	Length of time shut-in		SI press. p CSG TBG	esig		Stabilized? (Ye	es or No)
Lower Hour, date sh	Length of time shut-in	Length of time shut-in		SI press, psig TBG		Stabilized? (Ye	s or No)	

(Continue on reverse side)

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Commenced at (hour, date	9)*		FLOW IEST NO	Zone producing (Upper or	Lower)* UPPER
TIME (hour, date)	LAPSED TIME SINCE*	PRES Upper Completion	SURE Lower Completion	PROD. ZONE TEMP.	REMARKS
		CSG			
		TBG	TBG		
		CSG			
		TBG	TBG		
	İ	CSG	i i		
	i	TBG	TBG		
	j	İ	j j		
	l				
	ĺ		i i		
			[]		
]		
		-	1		
Production rate during		pased on	Did. in	Harris	C
Oil:	воры	based on	Bbls. in	Hours.	Grav. GOR
Gas:	, , , , , , , , , , , , , , , , , , ,	MCFPD; Tes	ted-thru (Orifice or Me	eter):	
Remarks:					
		···			
hereby certify that th	e information herein co		pete to the best of my	-	
Approved	AUG 1	19	Ope	erator UNION OIL O	F CALIFORNIA/dba UNOCAL
New Mexico Oil Co	onservation Division		_	mile	21.5
	On harman	Reliens	Ву	Mike Tabet	∠ ane
D.,	Land	Rolunaon Gas Inspector	m.		man
Ву	Deputy Oil 8	k Gas Inspector	Title	e Froduction Forer	IIdII
Γitle .			Date	e August 15th. 1	1997

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No.1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No.1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No.1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours test: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as a required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10 - 01 - 78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)