

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☐ Oil Well ☐ Gas Well ☒ Other Non-Commerical

2. Name of Operator

EnRe Corporation

Ampolex (USA), Inc. - AGENT

3. Address and Telephone No.

4940 Broadway, #200

1050 17th Street, Suite #2500

San Antonio, TX 78209

Denver, CO 80265

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Section 28-T27N-R2W

(303) 595-9000

455' FNL & 1,510' FEL

5. Lease Designation and Serial No.

701-94-0010

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Leavry Canyon 28B #1

9. API Well No.

30-039-25233

10. Field and Pool, or Exploratory Area

Gavilan - Mesa Verde

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

RECEIVED  
AUG 28 1996  
OIL CON. DIV.  
DIST. 3

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- Set cement retainer at 5,700' and squeeze perforations 5,753' - 6,263' gross interval with 50 sx cement. Put 5 sk plug on top of retainer.
- Placed 100' cement plugs as follows: 3,858'-3,958'; 3,393'-3,493' and 1,510'-1,610'.
- Pressure tested surface casing to 1000 psi. No bleed off.
- Placed 100' cemen tplug from 382' - 482' inside of 7-5/8".
- Cut off wellhead.
- Ran 50' of 1" pipe in surface casing and pumped cement to surface. Ran 1" in 7-5/8" an placed 50' cement plug.
- Installed steel plate and dry hole marker. Re-habilitated site.

cc: Oil & Gas Admin., Jicarilla Apache - Thurman Velarde ; EnRe Corporation

14. I hereby certify that the foregoing is true and correct

Signed

Robert C. Arceneaux

Title

Robert C. Arceneaux

Senior Petroleum Engineer

Date

19 August 1996

(This space for Federal or State office use)

Approved by

[Signature]

Chief, Lands and Mineral Resources

Date

AUG 26 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side