Distribution: O+4 (BLM); 1-Well File; 1-	Crystal; 1-Earleen, Sarak Mims	,
DEDART	UNITED STATES MENT OF THE INTERIOR OF LAND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
51/		5. Lease Designation and Serial No.
	CES AND REPORTS ON WELLS to drill or to deepen or reentry to a different reservoir	SF-079298-C 6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT-" for such proposals		7. If Unit or CA, Agreement Designation
SUBMIT IN TRIPLICATE 1. Type of Well		_
Oil Gas Well Other		8. Well Name and No.
2. Name of Operator MERRION OIL & GAS CORPORATION		Shelby Federal Com 1E 9. API Well No.
3. Address and Telephone No. P. O. Box 840, Farmington, New Mexico 87499 (505) 327-9801		30-039-25343 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Surv 800' FNL & 2030' FW		Basin Dakota 11. County or Parish, State
Section 24, T27N, R7		Rio Arriba, New Medico
	DX(s) TO INDICATE NATURE OF NOTICE, REPOR	
TYPE OF SUBMISSION	TYPE OF ACTION	JAN 0 4 1994
Notice of Intent	Abandonment	Change of Plans OIL CON.
Subsequent Report	Recompletion Plugging Back Casing Repair	New Construction Non-Routine Frecturing Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other TD & Casing Rpt	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
	te all pertinent details, and give pertinent dates, including estimated date of sta rtical depths for all markers and zones pertinent to this work.)*	
12/16/93 TD 7-7/8" hole at 7823'. L	ogged. Condition hole.	
	188 joints of 4-1/2", 11.6#, 10.5#, LTC & STC casint Stage as follows: pump 10 bbls WMW-1, followed	<u>-</u> -
586 sxs Class H with 3# sx	Hiseal, .50% CF14, (yield 1# cuft/sx, density 15.80 PD @ 6:25 PM 12/17/93. Press up well, establish c	#/gal. Displace cement with 30 bbls
Cmtd 2nd stage as follows: pump 10 bbls water ahead of 200 sxs 65/35 lite with 8% gel, 2% CaCl, 6# sx Hiseal, .25#/sx cello-seal, yield 2.03 cuft/sx, density 12.20#/gal. Displace cement with 30 bbls water		
followed by 58 bbls mud. PD @ 11:15 PM 12/17/93 - held good. Press up well, establish circulation. Cmtd 3rd Stage		
	vater ahead of 550 sx 65/35 lite with 8% gel, 2% Ca with 50 sx Class B with 2% CaCl & 3# sx, yield 1	•
	5:05 AM 12/18/93. Circ approx 20 bbls cmt to surf	
14. Thereby certify that the foregoing is true and correct/		
Signed Signed Signed	Title Operations Manager	12/23/93
(This space for Federal or State office use)		
Approved by	D	* PIED FOR RECORD
	knowingly and willfully to make to any department or agency of the United Sta	tes any false, fictitious or fraudulent statements
*See Instruction on Reverse Side		

FARMINGTON DISTRICT OFFICE BY