

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

JUL - 5 1995

5. Lease Designation and Serial No.
SF-080385

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
RINCON UNIT

8. Well Name and No.
RINCON UNIT #178E

9. API Well No.
30-039-25434

10. Field and Pool, or Exploratory Area
Basin Dakota/Blanco

11. County or Parish, State
Mesaverde
Rio Arriba, NM

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
UNION OIL COMPANY OF CALIFORNIA

3. Address and Telephone No.
P.O. BOX 2620, Casper, WY 82602 (307) 234-1563 Ext. 116

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1450' FSL & 1450' FEL
Sec. 23, T27N-R7W

OIL CON. DIV.
DIST. 3

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
- ☐ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other SPUD REPORT

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU Aztec Well Service Rig #184. Drill rat & mouse hole. Spud 12.25" hole @ 1630 hrs. 6-20-95. Drld to 376' TD. TOH. Ran & cemented 8 jts. 361' 9.625 36# J-55 ST&C new casing, landed @ 376'. Mixed & pumped 250 sx Class "G" cmt w/2% Cacl2, .25# flo-seal, (mixed @ 15.8 ppg, yield 1.16 cu.ft.), displaced w/26 bbls. water. Circulated 75 sx cement to surface. Closed in. WOC 5.5 hrs. NUBOP & test BOP to 380# low and 2100# high. PU bit, TIH test pipe rams, kelly & floor valves & casing to 2100# high and 380# low. Drill 75' cement & shoe. Drilled to 897'. Ran survey. Drilled to 950'.

DZO FARMINGTON, NM

25 JUN 27 AM 10:34

RECEIVED
BLM

14. I hereby certify that the foregoing is true and correct

Signed

Title Drilling Superintendent

Date 6-23-95

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

FARMINGTON DISTRICT OFFICE