STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page Revised 10/01/7

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

-		on Oil Compa	ny of Califo	ornia lease_	Rinc	on Un	it	Weil No.	#178E	
ocation of Well:	Unit	J Sec23			7W		Co	untyR	io Arriba	
	" NAME OF RESERVOIR OR POOL		TYPE OF F		METHOD OF PROD. (Flow or Art, Litt)			PROD. MEDIUM (Tog. or Cag.)		
Upper Completion				Gas	Gas		Flow .		Tubing	
Lewer Completion	Basin Dakota			Gas	Gas		Flow		Tubing	
			PRE-FL	OW SHUT-IN P	RESSURE	DATA				
Upper Completion		/95 8:00am	<u></u>	Days	&I press. psig	Tbg. 560		1	Milized? (Yes or No) Yes	
Lewer Completion	10/03		Length of time and	uun Days	SI press. psig	Tbg. 850		Stabilized? (Stabilized? (Yes or No) NO	
		,		FLOW TEST	NO. 1					
on-meneed	at thour, da	•••• 10/09/95	8:20am		Zone pred	ucing (Up	per er Lowerk	Lower		
TIME (hour, date)		LAPSED TIME SINCE*	PRES Upper Completion	Lower Completion	PROD. ZONE TEMP.		REMARKS			
9:20	1:20 am 1 Hr.		Csg. 980 Tbg. 560	Tbg. 650	70	0	Q = 400 MCF/D			
10:20) am	2 Hrs.	Csg. 980 Tbg. 560	Tbg. 500			•			
11:20	am .	.3 Hrs.	Csg. 980 Tbg. 560	Tbg. 320						
	· · · · ·						ſ	可国的		
					ļ			ili oct	1 8 1895	
	′× .									
roductio	on rate d	wing test		•				D	II. I	
)il:	··· .	BOP	D based on	Bbls. is	a	Hours	•	Grav	GOR	
કેથ:		ter I villa e	мсг	PD; Tested thru	(Orifice o	Meter	·):			
· · · · · · · · · · · · · · · · · · ·		-	мір-ті	EST SHUT-IN P						
Ompretien	10/09	/95 11:30a		Days	St press, paig		980 - 560	Slabilized? (1	NO NO	
Lower completion	10/09		Length of time shi	Days	SI press. paig	Tbg.	860	Stabilized? ()	Yes or Hop Yes	

(Continue on reverse side)

FLOW TEST NO. 2

menced at (hour, date) ** 10/16/95 11:40 am				Zone producing (Upper or Lewert Upper			
TIME	LAPSED TIME SINCE ##	PRESEURE		PROD. ZONE			
(hour, date)		Upper Completion	Lewer Completion	TEMP.	REMARKS		
12:40 pm	1 Hr.	Tbg. 460	Tbg. 860	68°	Q = 160 MCF/D		
1:40 pm	2 Hrs.	Csg. 780 Tbg. 260	Tbg. 860				
2:40 pm	3 Hrs.	Csg. 550 Tbg. 350	Tbg. 860				

Production rate during	g test					
Oil:	BOPD based on	В	bls. in	Hours.	Grav	GOR
Gas:	М	CFPD: Tested	thru (Orifice o	or Meter):		·
Remarks:				·		
		: 				
I hereby certify that the	he information herein cont	ained is true :	and complete to	the best of n	ny knowledge.	
Approved Jeh	nny Robert	19	Operator	Union Oil	Company of	California dba
	OCT 2 0 1995		Ву	J. J.	iese	Unocal
By	Y 01L 7 (488)		Title	General C	lerk	
Title	T. C.	•	Date	October 1	7, 1995	

NORTHWEST NEW MEDICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 11, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test 'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minuse intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the teachation of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone texts: all pressures, throughout the entire text, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at feast twice, once at the beginning and once at the end of each east, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described sens shall be filed in replicate within 13 days after completion of the text. Texts shall be filed with the Aster District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Text Form Revised 18-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

RLC/skl