

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other Non-Commercial

2. Name of Operator

EnRe Corporation

Ampolex (USA), Inc. - AGENT

3. Address and Telephone No.

4940 Broadway, #200
San Antonio, TX 78209

1050 17th Street, Suite #2500
Denver, CO 80265

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Section 18-T27N-R2W

1,450' FSL & 1,070' FEL

(303) 595-9000

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

701-94-0010

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Leavry Canyon 18I #2

9. API Well No.

30-039-25470

10. Field and Pool, or Exploratory Area

Gavilan - Pictured Cliffs

11. County or Parish, State

Rio Arriba Cty, N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Set cement retainer @ 3,550' and squeezed 50 sx cement to abandon perforation 3,574' - 3,596'. Placed 5 sx plug on top of retainer.

2. Placed cement plug from 3,200' - 3,100' (12 sx).

3. Placed cement plug from 1,560' - 1,460' (12 sx).

4. Pressure tested surface casing to 1,000 psi. No leak off.

5. Placed cement plug from 325' - 225' (12 sx).

6. Cut off wellhead. Ran 50' of 1" inside of 9-5/8" surface and filled annulus to surface with cement. Ran 1" inside of 4-1/2" casing and filled same to surface with cement. Weld on steel plate and dry hole marker. Rehabilitate wellsite.

CC: Oil & Gas Admin., Jicarilla Apache - Thurman Velarde ; EnRe Corporation

14. I hereby certify that the foregoing is true and correct

Signed

Robert C. Arceneaux - AGENT

Title

Senior Petroleum Engineer

Date 05 August 1996

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Chief, Lands and Mineral Resources

Title

Date AUG 26 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side