

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Non-Commercial

2. Name of Operator

EnRe Corporation

3. Address and Telephone No.

4940 Broadway, Suite #200
San Antonio, TX 78209

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Section 18-T27N-R2W
1,015' FNL & 790' FEL

Ampolex (USA), Inc. - AGENT

1050 17th Street, Suite #2500
Denver, CO 80265

(303) 595-9000

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

701-94-0010

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Leavry Canyon 18A #1

9. API Well No.

30-039-25473

10. Field and Pool, or Exploratory Area

Gavilan - Pictured Cliff

11. County or Parish, State

Rio Arriba County, N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Set cement retainer @ 3,700' and squeezed perfs. 3,760' - 3,792' with 50 sx and placed 5 sx on top.
- Placed cement plug from 3,200' - 3,100' (12 sx).
- Placed cement plug from 2,770' - 2,670' (12 sx).
- Perforated 4-1/2" casing @ 325'. Could not circulate to surface. Bullhead cement (50 sx) down 4-1/2" (verbal approval from Mr. R. Kent, BLM). Tagged top of cement @ 197' with tubing.
- Cut off wellhead. Set 50' cement plugs inside 4-1/2" and 9-5/8" surface casing thru 1" pipe.
- Weld on steel plate and dry hole marker. Rehabilitate wellsite.

cc: Oil & Gas Admin., Jicarilla Apache - Thurman Velarde ; EnRe Corporation

14. I hereby certify that the foregoing is true and correct

Robert C. Arceneaux - AGENT

Signed *Robert C. Arceneaux*

Title Senior Petroleum Engineer

Date 5 August 1996

(This space for Federal or State office use)

Approved by *Don R. [Signature]*

Title Chief, Lands and Mineral Resources

Date AUG 26 1996

Conditions of approval, if any: