

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 079364

6. If Indian, Allottee or Tribe Name

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

UNION OIL COMPANY OF CALIFORNIA

3. Address and Telephone No.

P.O. BOX 2620, Casper, WY 82602 (307) 234-1563 Ext. 116

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1505' FNL & 1850' FWL (SE NW)

Sec. 31, T27N-R6W

7. If Unit or CA, Agreement Designation

RINCON UNIT

8. Well Name and No.

RINCON UNIT #176E

9. API Well No.

30-039-25490

10. Field and Pool, or Exploratory Area

Basin Dak/Blanco M.V.

11. County or Parish, State

Rio Arriba CO., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

SPUD REPORT

(Note: Report results of multiple completion or Completion or Recompletion Report and Log.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU Aztec Well Service Rig #222. Spud 12 $\frac{1}{4}$ " hole at 5:30 p.m. 7-27-95. Drilled to 375'. Drop survey and POOH. Ran and cemented 8jts 9-5/8" (356.81'), 36# J-55, new slm casing landed @ 370.81. Cemented w/225 sx Class "G" cement w/2% CaCl<sub>2</sub>, .25# flowseal (mixed @ 15.8 ppg, yield 1.15 cu.ft./sx. Circulated 50 bbls. cement to surface. Bumped plug. WOC 4 hrs. NUBOP. Tested 9-5/8" csg, blind rams, pipe rams, manifold and floor valves to 2300 psi. Held OK. Drilled cement and guide shoe. Drilled to 1075'. Drilling Inc.

14. I hereby certify that the foregoing is true and correct

Signed

TIM BENSON

Title

DRILLING SUPERINTENDENT

Date

8-1-95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side

FARMINGTON DISTRICT OFFICE