Form 3160-5 (June 1990)

1. Type of Weil

Oil Well

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budger Bureau No. 1004-0135

Expires: March 31, 1993 Kease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

SF 080385

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals · 55 /103 21 PH 1:50

SUBMIT IN TRIPLICATE

37-25-52-

7. If Unit or CA, Agreement Designa RINCON UNIT 8. Well Name and No. RINCON UNIT #193M

2. Name of Operator UNION OIL COMPANY OF CALIFORNIA

X Gas Weil

3. Address and Telephone No. Ext. 116 (307) 234-1563

10. Field and Pool, or Exploratory Are Basin Dak/Blanco M.V.

9. API Weil No.

P.O. Box 2620, Casper, WY 82602

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

11. County or Parish, State

1000' FNL & 1190' FWL (NW NW) D-81- 211- 074

or representations as to any matter within its jurisdiction.

Rio Arriba, NM

(Note: Report results of multiple completion c Completion or Recompletion Report and Log

	TO MINIOR TO MATURE OF NOTICE REPORT OR OTHER DATA		
12.	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
	TYPE OF SUBMISSION	TYPE OF ACTION	
	Notice of Intent  Subsequent Report  AU6 2  Final Abandonment	Plugging Back  Casing Repair  Altering Casing	Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off  Conversion to Injection  Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU Aztec Well Service Rig #222. Spud 124" hole @ 12:00 a.m. 8-11-Drilled to 378'. Drop survey and POOH. Ran and cemented 8 95. (355') 9-5/8", 36# J-55, ST&C new casing landed @ 365'. Cemented w/250 sx Class "G" cement w/2% Cacl2, .25#/sx D-29 (mixed @ 15.8 ppg, yield 1.15 cu.ft./sx) circulated 60 sx good cement to Tested 9-5/8" csq, Bumped plug. WOC 4 hrs. NU BOP. surface. blind rams, pipe rams, manifold and floor valves to 2300 psi. Drilled cement and guide shoe. Drilled to 1613', drilling inc.

14. I hereby certify that the foregoing is true Drilling Superintendent Date (This space for Federal or State office use) Date Title Approved by Conditions of approval, if any: ACCEPTED FOR RECORD Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent states.

\*See instruction on Reverse Side

FARMINGTON DISTRICT OFFICE

MAKICO