+Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Fonn C-103

OIL CONGEDIATION DIVIDION

Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobby NM 88240	OIL CONSERVATION		WELL API NO.	
	P.O. Box 2088		30-039-25544	
DISTRICT 11 P.O. Drawer DD, Artesia, NM 88210	Santa re, New Mexico	8/304-2088	S. Indicate Type of	FLease STATE FEE
DISTRICT 111 1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil ,& Gas	
			·	
(DO NOT USE THIS FORM FOR PRO DIFFERENT RESER	CES AND REPORTS ON WE PPOSALS TO DRILL OR TO DEEPEN RVOIR. USE *APPLICATION FOR PI *101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A	7. Lease Name or U	Init Agreement Name
I. Type of Well: OIL WELL GAS WELL WELL	OTHER		SAN JUAN 28-	.7 UNIT
2 Name of Operator			8. Well No.	7 01111
CONOCO IN	C		1301	
3. Address of Operator 10 DESTA DR. STE 100W, MIDLAND, TX. 79705-4500			9. Pool name or Wildcat BASIN DAKOTA 71599	
4. Well Location	V, MIDEAND, 17. 19100-4000		L BASIN DA	KUIA /1399
Unit LetterD808	Feet From The NORTH	Line and1182	Feet From	The WEST
Section 2	Township 27 N R		NMPM Rio Arri	iba County
<u> </u>	/////// GL 6120'			. N 1 N 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1
	Appropriate Box to Indicate			
NOTICE OF INT	ENTION TO:	SUB	SEQUENT R	EPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING		CASING TEST AND CE	EMENT JOB	
OTHER		OTHER SPUD, SET	SURFACE CSG	\[
12. Describe Proposed or Completed Operation work) SEE RULE 1103. 10-23-96 MIRU Axtec Rig #124. Sp Shoe set @ 364.40', collar set @ 320. fresh water. Cement returns to surface pm on 10-23-96.	oud 12 1/4" hole, drill to a depth of 25'. Lead slurry 215 sx Class 'B'	of 365'. GIH W/ 8 jts cmt + 2% CACL2 + 1/	9 5/8", 36#, K-55 4#/sx Cello Flake	STC casing set @ 365'. Displaced W/ 24.8 bbl
Continue drilling 8 3/4" hole.			PEC	T TOSS
hereby certify that the information above is true	e and complete to the test of my knowledge an		The same of the sa	
SIGNATURE	parkly 11	Sr. Regulatory Sp	ecialist	DATE 10-29-96
TYPE OR PRINT NAME Bill R. Keathly	y			TELEPHONE NO. 915-686-54
This space for State Use)				
Original Signed by FRA	NNK T. CHAVEZ	SUPERVISOR DIS	STRICT#3	OCT 3 1 199
CONDITIONS OF AFPROVAL, IF ANY:				

+Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Fonn C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobby NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088

WELL API NO.

DISTRICT II Santa Fe, New Mexic	
P.O. Drawer DD, Artesia, NM 88210	S. Indicate Type of Lease
DISTRICT 111 1000 Rio Brazos Rd., Aztec, NM 87410	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil ,& Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WOOD DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEP DIFFERENT RESERVOIR. USE *APPLICATION FOR (FORM C-101) FOR SUCH PROPOSALS.)	EN OR PLUG BACK TO A
1. Type of Well:	
OIL GAS WELL OTHER	SAN JUAN 28-7 UNIT
2. Name of Operator CONOCO INC.	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
10 DESTA DR. STE 100W, MIDLAND, TX. 79705-45	
4. Well Location	
Unit Letter <u>D</u> 808 Feet From The NORTH	Line and 1182 Feet From The WEST
Section 2 Township 27 N	Range 7W NMPM Rio Arriba Country
	Range 7W NMPM Rio Arriba County
//////////////////////////////////////	
	e Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	1
	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB
OTHER	OTHER SET INTERMEDIATE CSG
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, work) SEE RULE 1103. 10-26-96 DRILL 8 3/4" HOLE TO A DEPTH OF 3035'. GIH W/collar set @ 2990'. Lead slurry 305 sx 35/65 Poz & Class 'B' cmt + 'B" cmt + 2% CACL2 + 1/4#/sx Cello Flake. Displaced W/ 118.16 2:20 pm on 10-26-96 W/ 1200 psi. Notified BLM & NMOCD @ 6:	81 jts 7" 23#, N-80, LT&C casing set @ 3035'. Shoe set @ 3035', 8% Gel + 2% CACL2 + 1/4#/sx Cello Flake. Tail slurry 115 sx Class obl Fresh Water. Cement returns to surface of 9 sx. Bumped plug @
_	10 to 10 20 ye.
Continue drilling 6 1/4" hole toward total depth.	V sa
I hereby certify that the information above is true and complete to the test of my knowledge	and blief
Bill Serren	Sr. Regulatory Specialist 10-29-96
SIGNATURE	TITLE DATE DATE
TYPE OR PRINT NAME Bill R. Keathly	TELEPHONE NO. 915-686-542
This space for State Use)	
	SUPERVISOR DISTRICT # 2 OCT 7 4 420
This space for State Use) Original Signed by FRANK T. CHAVEZ	SUPERVISOR DISTRICT # 3 DATE OCT 3 1 199