

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

RECEIVED
OCT 21 1996

96 OCT 16 PM 1:25
070 FARMINGTON, NM

OIL CON. DIV.
DIST. 3

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

2380' FSL, 905' FEL, Sec. 1, T-27-N, R-5-W, NMPM

NSL-3706

I

Lease Number
SF-079491

If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 27-5 Unit

8. Well Name & Number

San Juan 27-5 U #100M

9. API Well No.

30-039-25591

10. Field and Pool

Blanco MV/Basin DK

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other -	

13. Describe Proposed or Completed Operations

10-6-96 Drill to intermediate TD @ 4442'. Circ hole clean. TOOH. TIH w/102 jts 7 5/8" 26.4# J-55 LT&C csg, set @ 4442'. Pump 10 bbl wtr, 10 bbl super flush, 10 bbl wtr ahead. Cmdt w/53 sx Class "B" 65/35 poz w/6% gel, 0.25 pps Cellophane, 5 pps Gilsonite (98 cu.ft.). Tailed w/100 sx Class "B" neat cmt w/2% calcium chloride, 0.25 pps Cellophane, 5 pps Gilsonite (118 cu.ft.). Circ 5 bbl cmt to surface. Stage tool set @ 3922'. Cmdt second stage w/851 sx Class "B" 65/35 poz w/6% gel, 0.25 pps Cellophane, 2% calcium chloride, 5 pps Gilsonite (1574 cu.ft.). Tailed w/100 sx Class "B" neat cmt w/2% calcium chloride, 0.25 pps Cellophane (118 cu.ft.). Circ 70 bbl cmt to surface. WOC.

10-7-96 WOC. PT csg to 1500 psi/15 min, OK. Circ hole clean. Drilling ahead.

10-10-96 Drill to TD @ 8589'. Circ hole clean. TOOH.

10-11-96 TIH w/101 jts 5 1/2" 17# K-55 LT&C lnr, set @ 8589'. Top of lnr @ 4257'. Pump 5 bbl wtr, 10 bbl super flush 5 bbl wtr ahead. Cmdt w/585 sx Class "G" 50/50 poz w/3% fluid loss, 0.25 pps Cellophane, 3 pps Gilsonite (807 cu.ft.). Reverse out 20 bbl cmt to surface. PT lnr to 3000 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed *Debra Draughn* Title Regulatory Administrator Date 10/15/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

OCT 16 1996

FARMINGTON DISTRICT OFFICE

RY

NMOCD