

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE.

Southeastern New Mexico

T. Anhy

T. Salt

B. Salt

T. Yates

T. 7 Rivers

T. Queen

T. Grayburg

T. San Andres

T. Glorieta

T. Paddock

T. Blinebry

T. Tubb

T. Drinkard

T. Abo

T. Wolfcamp

T. Penn

T. Cisco (Bough C)

T. Canyon

T. Strawn

T. Atoka

T. Miss

T. Devonian

T. Silurian

T. Montoya

T. Simpson

T. McKee

T. Ellenburger

T. Gr. Wash

T. Delaware Sand

T. Bone Springs

T.

T.

T.

T.

Northwestern New Mexico

T. Ojo Alamo

T. Kirtland-Fruitland

T. Pictured Cliffs

T. Cliff House

T. Menefee

T. Point Lookout

T. Mancos

T. Gallup

Base Greenhorn

T. Dakota

T. Morrison

T. Todilto

T. Entrada

T. Wingate

T. Chinle

T. Permian

T. Penn "A"

2155

2240-2710

3033

4500

4828

5200

5675

6450

7150

7362

T. Penn. "B"

T. Penn. "C"

T. Penn. "D"

T. Leadville

T. Madison

T. Elbert

T. McCracken

T. Ignacio Otzte

T. Granite

T. Lewis - 3113

T. Huerfano Bent - 3530

T. Chacra - 3590

T. Graneros - 7280

T.

T.

T.

T.

OIL OR GAS SANDS OR ZONES

No. 1, from

No. 2, from

to

to

No. 3, from

No. 4, from

to

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from

No. 2, from

No. 3, from

to

to

to

feet

feet

feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
2155	2240		White, cr-gr ss.	5675			Dark gry carb sh.
2240	2710		Gry sh interbedded w/tight, gry, fine-gr ss	6450			Lt gry to bm calc carb micac glau silts & very fine gr gry ss w/irreg. interbedded sh
2710	3033		Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss	7150	7280		Highly calc gry sh w/thin lmst
3033	3113		Bn-gry, fine grn. tight ss	7280	7362		Dk gry shale, fossil & carb w/pyrite incl
3113	3530		Shale w/siltstone stringers	7362	7493		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks
3530	3590		White, waxy chalky bentonite				Perforations continued: 5268, 5280, 5288, 5300, 5308 5316, 5334, 5338, 5402, 5426, 5470, 5518, 5540, 5552, 5566, 5572
3590	4500		Gry fn grn silty, glauconitic sd stone w/drk gry shale				
4500	4828		ss. Gry, fine-grn, dense sil ss.				
4828	5200		Med-dark gry, fine gr ss, carb sh & coal				
5200	5675		Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation				