

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1525' FSL, 1950' FEL, Sec. 18, T-27-N, R-4-W, NMPM, Rio Arriba County

API # (assigned by OCD)

30-039-25853

5. Lease Number

Fee

6. State Oil & Gas Lease #

7. Lease Name/Unit Name

San Juan 27-4 Unit

8. Well No.

44E

9. Pool Name or Wildcat

Basin Dakota

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other - Spud

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

8-6-98 MIRU. Spud well @ 5:30 p.m. 8-6-98. Drill to 330'.

8-7-98 Drill to 525'. Circ hole clean. TOOH. TIH w/12 jts 9 5/8" 32.3# H-40 ST&C csg, set @ 520'. Pump 40 bbl wtr ahead. Cmdt w/225 sx Class "B" neat cmt w/3% calcium chloride, 0.25 pps Cellophane (266 cu.ft.). Displace w/37.5 bbl wtr. Circ 37 bbl cmt to surface. WOC. NU BOP. PT csg & BOP to 600 psi/30 min, OK. TIH w/8 3/4" bit to 148'. Csg backed off 3 jts down. TOOH. TIH w/8 3/4" bit. CO cmt @ 148-155'. Tag top of csg. Unable to enter csg. TOOH. TIH w/3 1/2" drill pipe to 155'. (Verbal approval to plug and abandon from Frank Chavez, OCD). Pump 3 bbl wtr ahead. Pump 90 sx Class "B" neat cmt w/3% calcium chloride, 0.25 pps Cellophane (106 cu.ft.) down csg. Circ 90 bbl cmt to surface. WOC.

8-8-98 WOC. Well plugged and abandoned 8-8-98.

SIGNATURE
no



Regulatory Administrator August 20, 1998

(This space for State Use)

ORIGINAL SIGNED BY E. VILLANUEVA

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Approved by

Title

Date

MAY 17 1999