

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1045' FSL, 1665' FEL, Sec. 24, T-27-N, R-5-W, NMPM

5. Lease Number  
SF-079492-B

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name  
San Juan 27-5 Unit

8. Well Name & Number  
San Juan 27-5 U #119M

9. API Well No.  
30-039-25935

10. Field and Pool  
Blanco MV/Basin DK

11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☐ Abandonment

☐ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Spinner Survey

13. Describe Proposed or Completed Operations

It is intended to run a spinner survey on the subject well according to the attached procedure and wellbore diagram.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 8/13/99  
trc

(This space for Federal or State Office use)

APPROVED BY [Signature] Title \_\_\_\_\_ Date SEP 10 1999

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMCCO

## **San Juan 27-5 Unit #119M**

Unit O, Section 24, T27N, R05W

Rio Arriba County, New Mexico

Elevation 6609' GL, 6621' KB

LAT: 36° 33.3' Long: 107° 18.3'

### **Summary:**

The San Juan 27-5 Unit #119M was spudded in January of 1999 and was originally completed in the Dakota, Point Lookout, Menefee, Cliff House, and Lewis in four stages. A spinner survey will be run on this well to help quantify the contribution of the Lewis in the 27-5 Unit. This data, along with data from other spinner surveys and the Shale Data Wells, will also be used in the completion design optimization of the Lewis.

### **Procedure:**

1. Comply with all NMOCD, BLM, and BR regulations. Conduct daily safety meetings for all personnel on location.

**DO NOT KILL WELL. ANY FLUIDS USED IN WELLBORE WILL INVALIDATE DATA. IF FLUIDS ARE REQUIRED, CONTACT MICHELE QUISEL TO DISCUSS ALTERNATIVES.**

2. Inspect location and wellhead and install rig anchors prior to rig move if needed.
3. RU slickline unit. RIH w/ slickline and set tubing choke in SN @ 7789 ' (1.76" ID). RD slickline unit.
4. MIRU. Check all safety equipment to insure proper location and working order. ND wellhead and NU BOP, spool, stripping head and blooie line to pit. Continue to flow well through casing valve. Flow well through casing valve and blow well through blooie line to pit.
5. Strip 251 jts. 2-3/8" 4.7# J-55 tubing through stripping head and stand back. SI rams on BOP. ND stripping head. Place well back on production down the line.

**THE WELL WILL REMAIN ON PRODUCTION DURING THE ENTIRE SPINNER SURVEY.**

6. RU Schlumberger and full lubricator. Open rams on BOP and RIH w/ spinner flowmeter tool/GR/CCL/Gradio. Correlate depth to GR/CCL logs provided by the engineer on location.
7. Take spinner survey readings at the following stations:

• Station #1	4200'	Top of Navajo City
• Station #2	4400'	Top of Otero Chacra
• Station #3	4700'	Top of Middle Bench
• Station #4	4970'	Top of Upper Cliff House
• Station #5	5050'	Top of Massive Cliff House
• Station #6	6100'	Top of Dakota

## San Juan 27-5 Unit #119M

Unit O, Section 24, T27N, R05W

Rio Arriba County, New Mexico

Elevation 6609' GL, 6621' KB

LAT: 36° 33.3' Long: 107° 18.3'

8. Tag bottom w/ spinner tool. POOH w/ spinner flowmeter tool/GR/CCL/Gradio and SI rams on BOP. RD and release Schlumberger.
- 9A. If fill, TIH w/ 3-7/8" bit and CO to PBTD. TOOH.
9. NU stripping head. Open rams on BOP. Strip 251jts. 2-3/8" 4.7# J-55 tubing w/ expendable check and seating nipple one joint off bottom and land tubing @ 7822'. ND stripping head, BOP, spool, and blooie line. NU wellhead. Pump off expendable check. Place well on production. RD and release rig.

Recommend: Michele S. Quisel  
Production Engineer 8-6-99

Approve: Bruce W. Dyer 8-13-99  
Drilling Superintendent

Approve: [Signature] 8/7/99  
Team Leader

### Vendors:

Wireline: Schlumberger 328-5006

Michele Quisel	Office: 324-6162	Pager: 326-8196	Home: 564-9097
Steve Campbell	Office: 326-9546	Pager: 564-1902	Home: 325-8218
Hans Dube	Office: 326-9555		Home: 564-9401
Glen Christiansen	Office: 326-9733		Home: 327-5089

# San Juan 27-5 Unit #119M

1045' FSL, 1665' FEL

Unit O Sec. 24, T-27 R-05W

Rio Arriba County, New Mexico

KB 6621

GL 6609

LAT: 36 33.3'

LONG: 107 18.3'

9-5/8" 32.3# H-40  
180 sks TOC circ

243

8-3/4" Hole  
7" 23 # J-55  
440sx

TOC circ

2087

3630

6-1/4" Hole  
4-1/2" 10.5# J-55  
525 sks TOC TOL by CBL  
Liner: 2087 to 7857

Tubing: 2-3/8" 4.7# J-55 EUE  
@ 7822

PBTD 7856  
TD 7860

## Formation Tops

Ojo Alamo	2822
Kirtland Shale	3020
Fruitland Coal	3105
Pictured Cliffs	3376
Lewis	3510
Huer. Bent.	3955
Navajo City	4012
Otero Chacra	4415
Middle Bench	4550
Upper Cliff House	4988
Massive Cliff House	5098
Menefee	5244
Point Lookout	5610
Mancos	6099
Gallup	6800
Greenhorn	7529
Dakota	7722

### Lewis:

4226, 28, 30, 4418, 20, 22, 24, 26, 4578, 80, 82, 84,  
4714, 16, 18, 4842, 44, 46, 48  
Frac w/ 70Q Foam, 200,000# 20/40 sand

### Upper Menefee--Cliff House

4998, 5012, 28, 38, 76, 89, 5100, 12, 24, 32, 39, 55, 70, 86, 96,  
5218, 28, 38, 52, 70, 86, 5305, 11, 16, 26, 36, 45, 53, 79, 98, 5418, 35, 56  
Frac w/ SW, 100,000 # 20/40 sand

### Point Lookout--Lower Menefee:

5541, 60, 74, 87, 5602, 12, 17, 32, 44, 54, 58, 79, 95,  
5712, 27, 36, 49, 5803, 20, 36, 42, 61, 69, 92, 5908, 34, 47, 65, 86, 6065, 83  
Frac w/ SW, 100,000 # 20/40 sand

### Dakota:

7622, 24, 26, 28, 94, 96, 7742, 44, 46, 48, 50, 92, 94, 96,  
7818, 20, 22  
Frac w/ 20# X-Link Gel & 78,000# 20/40 TLC sand

08/06/1999

MSQ