submitted in lieu of Form 3160-5

ហ	NI TE	ED ST	ATI	ES
DEPARTM	ENT	OF T	ΗE	INTERIOR
BUREAU	OF	LAND	M	ANAGEMENT

	Notices and Reports on Wells
m	93 COT -7 TH 2: 34 5. Lease Number SF-080670 6. If Indian, All. o
Type of Well GAS	Tribe Name
Name of Operator	Unit Agreement Na
BURLINGTON RESOURCES	your or
	San Juan 27-4 Uni San Juan 27-4 Uni Prator San Juan 27-4 Uni San Juan 27-4 U
Address & Phone No. of Ope PO Box 4289, Farmington,	NM 87499 (505) 326-9700 UL 2 6 1909. API Well No. 30-039-25944
Location of Well, Footage 1880'FNL, 790'FWL, Sec.30	, T-27-N, R-4-W, NMPM DIST 3 11. County and State
NSL-4078, DHC-2063	Rio Arriba Co, NM
. CHECK APPROPRIATE BOX TO	INDICATE NATURE OF NOTICE, REPORT, OTHER DATA
Type of Submission	Type of Action
X Notice of Intent	Recompletion New Construction
Subsequent Report	Plugging Back Non-Routine Fracturing
Final Abandonment	Casing Repair Water Shut off X Altering Casing Conversion to Injection
	Other -
. Describe Proposed or C	Completed Operations
-	
It is intended to alte	er the approved surface casing depth and cement of the
It is intended to alte subject well. T	
It is intended to alte	er the approved surface casing depth and cement of the
It is intended to alte subject well. The Revisions:	er the approved surface casing depth and cement of the
It is intended to alte subject well. T	er the approved surface casing depth and cement of the
It is intended to alte subject well. The Revisions: Casing Program: Hole Size Dept	er the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'.
It is intended to alte subject well. The subject well and subject well as the subject well. The subject well as the subject well as the subject well. The subject well as the subj	er the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'.
It is intended to alte subject well. The Revisions: Casing Program: Hole Size Dept	er the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'.
It is intended to alte subject well. The subject well well. The subject well. The subject well well. The subject well. The subject well well. The subject well well. The subject well. The subject well well. The subject well. The subject well. The subject well well. The subject well.	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3%
It is intended to alte subject well. The subject	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface).
It is intended to alte subject well. The subject	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3%
It is intended to alte subject well. The subject	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 2-500' 9 5/8" 32.3# Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface). Sing to 600 psi/30 minutes.
It is intended to alte subject well. The subject	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 2-500' 9 5/8" 32.3# Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface). Sing to 600 psi/30 minutes.
It is intended to alte subject well. The subject	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface). Sing to 600 psi/30 minutes.
It is intended to alte subject well. The subject well well. The subject well well as subject well. The subject well as subject well. The subject well as	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Ch Interval Casing Size Weight Grade H-40 - 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface). Sing to 600 psi/30 minutes.
It is intended to alte subject well. The subject	The approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. Character Casing Size Weight Grade H-40 The new surface casing depth will be a minimum of 500'. Character Casing Size Weight Grade H-40 The foregoing Size Weight Grade H-40 The surface casing depth and cement of the minimum of 500'. The surface casing depth and cement of the minimum of 500'. The surface casing depth and cement of the minimum of 500'. The surface casing depth will be a minim
It is intended to alte subject well. The subject well well as the subject well. The subject well well well as the subject well. The subjec	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. The new surface casing depth will be a minimum of 500'. The new surface casing depth will be a minimum of 500'. The new surface casing depth will be a minimum of 500'. Grade H-40 To 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface). Sing to 600 psi/30 minutes. The foregoing is true and correct. Title Regulatory Administrator Date 10/5/98 State Office use) Title Date
It is intended to alte subject well. The subject well well. The subject well. The su	the approved surface casing depth and cement of the The new surface casing depth will be a minimum of 500'. The new surface casing depth will be a minimum of 500'. The new surface casing depth will be a minimum of 500'. The new surface casing depth will be a minimum of 500'. Grade H-40 To 464 sx Class "B" cement with 0.25 pps Flocele and 3% cu.ft. of slurry, 250% excess to circulate to surface). Sing to 600 psi/30 minutes. The foregoing is true and correct. Title Regulatory Administrator Date 10/5/98 State Office use) Title Date

or agency of the United States any false, f matter within its jurisdiction.