## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

DUDMITUUGA IN TICA OF TOEM TOTAL

Sundry Notices and Reports on Wells		·
	5.	Lease Number NMSF-080668
1. Type of Well GAS	6.	If Indian, All. or Tribe Name
	7.	Unit Agreement Name
2. Name of Operator		
BURLINGTON COMPANY COMPANY	8.	San Juan 27-4 Unit Well Name & Number
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	San Juan 27-4 U #139 API Well No. 30-039-26539
4. Location of Well, Footage, Sec., T, R, M 1910'FSL, 1760'FEL, Sec.9, T-27-N, R-4-W, NMPM		Field and Pool Blanco MV/Basin DK County and State Rio Arriba Co, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, O	THER	DATA
Type of Submission  _X_ Notice of Intent Recompletion New Constant Subsequent Report Plugging Back Non-Rouse Casing Repair Water Si	tructine I	tion Fracturing Ef
Final Abandonment X Altering Casing Convers	ion to	o Injection
13. Describe Proposed or Completed Operations  It is intended to alter the submitted casing depths and cer	ment (	of the subject well.
Revisions:		
Mud Program:         Interval         Type         Weight         Vis.         Fluid Loss           200-3961'         LSND         8.4-9.0         30-60         no control           3961-8041'         Gas         n/a         n/a		1 13 13 14 14 14 14 14 14 14 14 14 14 14 14 14
Casing Program (as listed, the equivalent, or better):  Hole Size Depth Interval Csg.Size Wt. Grade  8 3/4" 0' - 3961' 7" 20.0# J-55		
6 1/4" 3861' - 8041' 4 1/2" 10.5# J-55		√ (ξ <b>)</b> %
Cementing Program:  7" intermediate casing alternative two stage: Stage collar 3181 sx Premium Lite cement with 3% calcium chloride, 0.25 pps Cellor loss, 0.4% sodium metasilicate. Tail with 90 sx Type III cmt w/1 Celloflake, 0.2% fluid loss. Second stage: 453 sx Premium Lite 0.25 pps Celloflake, 5 pps LCM-1, 0.4% fluid loss, 0.4% SMS (120 circulate to surface).  4 1/2" Production Liner - Cement to cover minimum of 100' of 4 1/2" x 7" overlap. Lead with cmt w/0.25 pps Celloflake, 0.3% CD-32, 6.25 pps LCM-1, 1% fluid excess to cement 4 1/2" x 7" overlap).	lake, % cal cmt wi 00 cu.	5 pps LCM-1, 0.4% fluid cium chloride, 0.25 pps th 3% calcium chloride ft., 100% excess to
14. Thereby certify that the foregoing is true and correct.	<del></del>	11 N O K : 200
Signed Title Regulatory Supervisor	Dat	e 5/30/02
(This space for Federal or State Office vse)	te _	

Title 18 U.S.C. Section 1001, makes it a crime for any person the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.