Submit 3 Copies To Appropriate District	/ State		Form C-103							
Office Energy, Minerals & Natural Resources						Revised March 25, 1999 WELL API NO.				
District I 1625 N. French Dr. Hobbs, NM 88240 District II OIL CONSERVATION DIVISION								39-26568	3	
District II 811 South First, Artesia, NM 88210	2040 South Pacheco					te Type STATE	of Lease	FEE 🗍		
District ID										
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV					6. State (Oil & G	as Lease N	No.		
2040 South Pacheco, Santa Fe, NM 87505					STATE					
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE"APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:						lame or 1	Unit Agreen	nent Name		
Oil Well Gas Well X Other						RINCON UNIT				
2. Name of Operator						8. Well No.				
PURE RESOURCES L.P.						130M				
3. Address of Operator P.O. BOX 850, BLOOMFIELD, NM 87413						9. Pool name or Wildcat Basin DK/Blanco MV				
4. Well Location										
Unit Letter I: 1881 feet from the South line and 667 feet fom the East line									line	
Section	32 Tow	nship <u>27N</u>	Range	06W	NMPM	RIO /	ARRIBA	_County		
	10. Elevatio	on (Show wheath	er DF,RKB,F	T,GR,etc.)						
6680' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data										
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:										
PERFORM REMEDIAL WORK	PLUG AND ABAND	ON []	REMEDIAL.	WORK			ALTERING	CASING		
TEMPORARILY ABANDON	CHANGE PLANS		COMMENC	E DRILLING	OPNS		PLUG AND ABANDON			
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TE				ADANDON	IMENT		
OTHER:			OTHER:		D	RILLING	G			
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompliation SEE ATTACHED SEE ATTACHED										
I hereby certify that the information	,	mplete to the be	st of my kno	vledge and	belief.			·		
SIGNATURE Julie	I C. DU	TI	rle	San Juan	Basin Foren	nan	_DATE _	03/13/0	0 1	
Type or print name		Micheal C. Pl	hillips			TEL	EPHONE NO.	(505) 6	32-1811	
APPROVED BY Conditions of approval, if any:	D BY CHAPLE T. PER	TI	TLE	on so	es inspeta	or bisi	MAR]	6 200	1	

PURE RESOURCES, INC.

RINCON UNIT #130M - 76.82% WI

Lease Well 521386-130M

MIRU BEARCAT RIG #1. SPUD IN @ 11:00 PM 3/2/01. DRLG 12-1/4" HOLE F/ 12-193' W/ ALL WT, 100+ RPM SPUD MUD. 3/3/2001

DRLG 12-1/4" HOLE F/ 210-380' W/ ALL WT, 100+ RPM SPUD MUD, 370 GPM, 1200 PSI. RUN 8 JTS 9-5/8" 36# STC CSG 3/4/2001

(360'). SET @ 372'. PUMP 10 BW, 250 SX (348 FT3) CLASS "B" W/ 2% CACL2, .25% CELLOFLAKE. DROP PLUG. DISPLACE W/

25.7 BW. PLUG DOWN @ 2:00 PM. CIRC 26 BBLS CMT TO RESERVE PIT.MU BIT #2, 8-3/4 GT-09C & TIH.

TIH, TAG CMT @ 328'. DRLG PLUG & CMT TO 380'. DRLG 8-3/4" HOLE F/ 380-1931' W/ WATER & POLY, GEL SWEEPS 35-45K, 3/5/2001

75-85 RPM

DRLG F/ 1931-2725' W/ 30-45K, 60-85 RPM, 1400 PSI, 336 GPM WATER & POLY, RU TO RUN 7" CSG. 3/6/2001

3/7/2001

RUN 65 JTS 7" 20# J-55 STC CSG (2719'), FC @ 2677'.CIRC CSG. PUMP 20 BBLS MUD FLUSH, 10 BW. LEAD W 365 SX (825 FT3/147 BBLS), 2% CACL2, 6.25 PPS LCM-1, .25 PPS CELLOFLAKE @ 12.1 PPG. TAILW/ 70 SX (97 FT3/17.3 BBLS) TYPE 111 W/ 2% CACL2, .25 PPS CELLOFLAKE @ 14.6 PPG @ 5 BPM, 120 PSI. DROP PLUG & DISPLACE W/ 108 BW @ 5 BPM. FINAL LIFT 750#. BUMP PLUG TO 1500 PSI. FLOAT HELD. CIRC 100 BBLS GOOD CMT TO PIT. PLUG DOWN ND BOPE, SET SLIPS W/ ALL

WT, CUT OFF 14' 7" CSG. INSTALL CSG SPOOL & TEST TO 3000 PSI. NU BOP, CSG, CHOKE & BLIND RAMS TO 1500 PSI.

DRLG PLUG, FC, CMT, SHOE & CMT TO 2725', DRLG 6-1/4" HOLE W/ AIR HAMMER F/ 2725-2900' W/ 2-4K, 40 RPM, 300 PSI, 3/8/2001

1000 SCFM AIR

DRLG F/ 2900-6434' W/ 2-4K, 40 RPM, 450 PSI AIR. DRLG F/ 6434-7622' W/ 2-4K, 40 RPM, 1800 SCFM N2, 350 PSI. 3/9/- 11/2001

RUN 183 JTS (7693') 4-1/2" 11.6# I-80 LTC CSG.RU BJ & BL9W HOLE. START OUT 2000 SCFM. SLIGHT CONDENSATE - NO 3/12/2001

DUST. INCREASE TO 4000 SCFM. BLOW HOLE CLEAN. PUMF 20 BBLS GEL WATER, 10 BBLS FW. LEAD W/ 83 SX "F" PREM HIGH STRENGTH LITE @ 11.9 PPG @ 5 BPM. TAIL W/ 525 SX "F" PREM H.S. LITE @ 12.5 PPG @ 5 BPM. DROP PLUG & DISPLACE W/ 117.5 BW @ 4 BPM. HAD GOOD LIFT. BUMP PLUG W/ 2250 PSI, FLOAT HELD. CIRC 60 BBLS GOOD CMT TO PIT.

RIG RELEASED @ 6:00 AM. CORRECTED TD 7633'.

CASING INFORMATION

CSG DEPTH SET 9 5/8" CSG - 36# STC 372 7" CSG - 20# STC 2719 4 1/2" CSG - 11.6# LTC 7633'

TD 7633'