

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. Jic Cont 95
2. Name of Operator ENERGEN RESOURCES CORPORATION	6. If Indian, Allottee or Tribe Name Jicarilla Apache
3. Address and Telephone No. 2198 Bloomfield Highway, Farmington, NM 87401	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FSL, 800' FWL, Sec. 36, T27N, R3W, N.M.P.M.	8. Well Name and No. Jicarilla 95 6B
	9. API Well No. 30-039-26574
	10. Field and Pool, or exploratory Area Blanco Mesaverde
	11. County or Parish, State Rio Arriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- Notice of Intent
- Subsequent Report
- Final Abandonment Notice

- Abandonment
- Recompletion
- Plugging Back
- Casing Repair
- Altering Casing
- Other _____

- Change of Plans
- New Construction
- Non-Routine Fracturing
- Water Shut-Off
- Conversion to Injection
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

03/05/01 SPUD @ 6:00 pm 03/04/01. Drill 12 1/4" hole to 247'. Ran 5 jts. 9 5/8" 36# J-55 ST&C casing, set @ 247'. RU Halliburton. Cement with 150 sks Class B, 2% CaCl2 and 1/4#/sk flocele (177 cu. ft.). Plug down @ 3:15 am 03/05/01. Circulate 25 sks cement to surface. RD Halliburton. WOC. NU BOP. Test BOP & casing to 600 psi - OK.

03/10/01 Ran 96 jts. 7" 20# J-55 ST&C casing, set @ 4150'. RU Halliburton. Cement with 550 sks Class B 65/35 poz, 6% gel, 10#/sk gilsonite, 1/2#/sk flocele, 2% CaCl2 (1078 cu. ft.). Plug down @ 6:40 am 03/10/01. Circulate 35 bbls cement to surface. RD Halliburton. WOC. Test BOP & casing to 1200 psi - OK.

14. I hereby certify that the foregoing is true and correct

Signed *Yicki Donaghey*

Title Production Assistant

Date 03/12/01

(This space for Federal or State office use)
W. DAVID

Lands and Mineral Resources

Approved by _____

Title _____

Date MAR 20 2001

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.