Submit 3 Copies 3 NMOCD to Appropriate District Office 1 File

State of New Mexico Energy, Minerals and Natural Resources Department

Form	C	-1	œ	
Revis	eđ	1-	1-	8

FEE L

1 WBU wios DISTRICTI 1 WBU W10 P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

STATE

WELL API NO.

30-045-05598

5. Indicate Type of Lease

6. State Oil & Gas Lease No.

	E-9707		
SUNDRY NOTICES AND REPORTS ON WEL	LS ////////////////////////////////////		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PER	OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name		
(FORM C-101) FOR SUCH PROPOSALS.)	West Bisti Unit		
1. Type of Well:	mest bisti onit		
OL QUE WELL OTHER			
2. Name of Operator	8. Well Na		
Dugan Production Corp.	157		
3. Address of Operator	9. Pool name or Wildcat		
P.O. Box 420, Farmington, NM 87499	Bisti Lower Gallup		
4. Well Location			
Unit Letter P: 660 Feet From The South	Line and 660 Feet From The East Line		
Section 36 Township 26N Rai	nge 13W NMPM San Juan County		
Section 30 Township 2010 Rai	DF, RKB, RT, GR, etc.)		
11. Check Appropriate Box to Indicate N	Vature of Notice, Report, or Other Data		
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON X	REMEDIAL WORK ALTERING CASING		
TEMPORARILY ABANDON . CHANGE PLANS .	COMMENCE DRILLING OPNS. PLUG AND ABANCONMENT		
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB		
отнея:	ОТНЕЯ:		
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, an work) SEE RULE 1103.	d give pertinent dates, including estimated date of starting any proposed		

Plug by setting Class B + 6% gel plugs as follows:

- 1. 100' plug across Gallup top @ 4680'.
- 2. Perforate 50' below Mesa Verde top @ 2100' and spot 100' plug inside and outside casing.
- 3. Perforate 50' below Pictured Cliffs top € 1190 and spot plug inside and cutside casing to cover Fruitland top @ 895'.
- 4. Perforate 50' below surface casing @ 212' and circulate cement to surface.

		DATE 6/30/92
		TELEPHONE NO.
÷.	•	
mu		- DATE
	mue Operations Manager	Modge and belief.