



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. USA - 078056  
Unit N

SUNDRY NOTICES AND REPORTS ON WELLS

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |                                     | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |                                     | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |                                     | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |                                     | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            |                                     |   |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 23, 1956

N. M. Federal "C" Lease

Well No. 7 is located 660 ft. from S line and 1980 ft. from E line of sec. 31

SE/4 of SE/4 26N 12W  
(1/4 Sec. and Sec. No.) (Twp.) (Range)

Bisti-Gallup San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~drill hole~~ <sup>ground</sup> above sea level is 6150 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill this well with rotary tools to a sufficient depth to test the Gallup Sand expected at 4650'.

We propose to set 200' of 905/8" OD 32.30# J-55 surface casing and cement to surface.

We propose to drill through the Gallup Sand section to a depth of approximately 5000' and if productive, to set 7" OD casing through the zone. We intend to use scratchers and centralizers and enough cement to cement at least 300' above the top of the pay zone.

We propose to gun perforate the casing and sand oil frac the formation during completion.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sunray Mid-Continent Oil Company

Address Box 128

Hobbs, New Mexico

By W. M. Starnett J. A. Parry

Title Hobbs Area Superintendent