NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS Revised 12-1-55 Pool BALLARD Formation PC County SAN JUAN Initial g Annual Special Date of Test 7-21-61 Lease Well No. Company RAYRE Unit Sec. St Twp. Rge. Purchaser Casing Wt. O. I.D. Set at Perf. To To Tubing 1 215 Wt. I.D. Set at 2705 Perf. To_____ Gas Pay: From To see L xG GL Bar.Press. Producing Thru: Casing Tubing Type Well Single-Bradenhead-G. G. or G.O. Dual Date of Completion: Packer Reservoir Temp. OBSERVED DATA Tested Through (Process) (Choke) (Meters) Type Taps Flow Data Tubing Data Casing Data (Prover) (Choke) Press. Diff. Temp. Press. Temp. Press. Temp. Duration No. (Line) (Orifice) of Flow $\circ_{\mathtt{F}}$. Size Size $\circ_{\mathbb{F}_{\bullet}}$ psig °F. h psig psig Hr. 541 541 118 169 110 3 11224 FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow No. Factor **Factor** Factor Q-MCFPD (24-Hour) $^{\prime}$ hwp $_{\mathbf{f}}$ psia $^{\mathrm{F}}\mathbf{g}_{_}$ F_{t} Fpv **@** 15.025 psia 12,366 120 9924 9443 1.012 1522 2. PRESSURE CALCULATIONS Gas Liquid Hydrocarbon Ratio_ _____cf/bbl. Specific Gravity Separator Gas •670 Gravity of Liquid Hydrocarbons_ __deg. Specific Gravity Flowing Fluid Pc Pc 305,809 (1-e⁻⁵) 1.1010 $P_{\mathbf{w}}$ $P_{\mathbf{t}}^2$ $(\mathbf{F_cQ})^2$ No. $(F_cQ)^2$ $F_{c}Q$ Cal. Pt (psia) (1-e-s) Pw JE, 787 273,946 Absolute Potential: MCFPD; n____ COMPANY BAR SERVICE. INC. ADDRESS FARMINGTON, NEW MEXICO BOX 1048 AGENT and TITLE J.W. SEAN, PRES. WITNESSED

REMARKS

^{ವಿಸ್ತ}ಿ: 3

COMPANY

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_w Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor. *
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.