(June 1990) DEDADTMENT OF	STATES, F THE INTERIOR D MANAGEMENT RECEIVED	PORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
BUKEAU OF LAND	BLM	5. Lesse Designation and Sorial No.
	REPORTS ON WELLS	SF 078155 6. If Indian, Allottee or Tribe Name
Do not use this form for proposals to drill or Use "APPLICATION FOR PEI	RMIT—" for such proposals	oir.
SUBMIT IN 1	TRIPLICATE 070 FARMINGTON, NM	7. If Unit or CA, Agreement Designation
1. Type of Well Cas Well Other P&A		West Bisti Unit
2. Name of Operator		8. Well Name and No. West Bisti Unit 154
Dugan Production Corp.		9. API Well No.
3. Address and Telephone No.		30-045-05614
P.O. Box 420, Farmington, NM 8 4. Location of Well (Footage, Soc., T., R., M., or Survey Description	37499 (505) 325-1821	10. Field and Pool, or Exploratory Area Bisti Lower Gallup
1980' FSL - 660' FEL		11. County or Parish, State
Sec. 35, T26N, R13W, NMPM		San Juan, NM
2. CHECK APPROPRIATE BOX(s) TO	INDICATE NATURE OF NOTICE, REI	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTI	ON
Notice of Intent	Abandonment	Change of Plans
(1) 11 1000 m 1000	Recompletion	New Construction
Subsequem Report MAY 2 7 1393		Non-Routine Fracturing
Final Abandonment Oll CON. D	Casing Repair Altering Casing	Water Shut-Off
DIST 3	Other	Conversion to Injection Dispose Water
(0.0.)		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
3. Perforate Mesa Verde at 2611. 4. Spot 77 cu. ft. class MBM cemer Mesa Verde plug 2411! - 2635!. 5. Perforate Pictured Cliffs at 13 6. Spot 85 sx class MBM cement at Fruitland plug 1007! - 1260!. 7. Cement down 5½m casing and retu 4% get followed by 35 cu. ft. Job complete 5-18-93.	nt with 2% CaCl ₂ at 2635'. Displace cemen 252'. 1260'. Displace cement to 1007'. No flow urn to bradenhead through hole at 413' wi	w back. Pictured Cliffs -
. I hereby certify that the foregoing is true and correct Signed John Weldander	Tide Operations Manager	Date 5/20/93
(This space for Federal or State office use)		
Approved by	Tide	Date
		AFFRUVEU

*See Instruction on Reverse Side

COOM

TO TONINGE