

OIL CONSERVATION DIVISION
P.O. Box 2083
Santa Fe, New Mexico 87504-2083

DISTRICT I
P.O. Box 1980, Hobbs, NM 83240

DISTRICT II
P.O. Drawer DD, Artesia, NM 83210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30 045 05621

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E 4500 3

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PLUG BACK (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒

GAS WELL ☐

OTHER ☐

2. Name of Operator

Dugan Production Corp.

3. Address of Operator

P. O. Box 420, Farmington, NM 87499-0420

7. Lease Name or Unit Agreement Name

Nest Bisti Unit

8. Well No.

148

9. Pool name or Wildcat

Bisti Gallup

4. Well Location

Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line

Section 36

Township 26N

Range 13W

NMCM

San Juan

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6190' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged well as follows:

1. Set cast iron bridge plug @ 4842'.
2. Spot 24 cu. ft. class "B" cement on top of CIBP from 4667' - 4842' as Gallup plug.
3. Perforate 5-1/2" casing @ 2005'.
4. Spot 47 cu. ft. class "B" cement at 2007'. Displace cement to 1805'. Mesa Verde plug 1805' - 2007'.
5. Perforate 5-1/2" csg @ 1270'. Set cement retainer set @ 905'.
6. Pump 201 cu. ft. class "B" cement below retainer. Pull out of retainer. Left 50' cement on top of cement retainer. Pictured Cliffs - Fruitland plug 855' - 1270'.
7. Perforate 5-1/2" casing @ 268'. Fill 5-1/2" casing & annulus with 153 cu. ft. class "B" cement. Surface plug 0' - 268'.

Job complete 7/14/98.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John Alexander

John Alexander

TITLE Vice-President

DATE July 28, 1998

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: