

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-01(35)
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Water Injection Well*

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL - 1980' FEL
Sec. 35, T26N, R13W, NMPM

5. Lease Designation and Serial No.

SF 078155

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 150

9. API Well No.

30-045-05622

10. Field and Pool, or Exploratory Area

*Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion Well Completion or Recompletion Report and Logform.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Set cast iron bridge plug @ 4850'.
2. Spot 24 cu. ft. class "B" cement on top of bridge plug. Gallup plug 4675' - 4850'.
3. Perforate 5½" casing @ 2030'. Spot 59 cu. ft. class "B" cement @ 2052'. Displace cement to 1880'. Mesa Verde plug 1880' - 2030'.
4. Perforate 5½" casing @ 1300'. Spot 181 cu. ft. class "B" cement w/4½ gel @ 1328'. Displace cement to 890'. Fruitland - Pictured Cliffs plug 890' - 1300'.
5. Perforate 5½" casing @ 264'. Establish circulation out bradenhead. Fill 5½" casing and 9-5/8" - 5½" annulus with 150 cu. ft. class "B" cement with 4½ gel.

Job complete 3-31-95.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Title

Operations Manager

Date

4-4-95

(This space for Federal or State Office Use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

DISTRICT MANAGER