



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 976154  
Unit SALCO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 13, 1959

Well No. Salco #6 is located 1900 ft. from [N] line and 1900 ft. from [E] line of sec. 14  
6 SW NE, Section 14 24N 13W New Mexico P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Blatt-Gallup San Juan County New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derriek floor above sea level is 6270 ft. GL

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

To drill and test subject well to the Gallup ss. Drilling Casing 9-5/8" OD casing to be set at approx. 200' KB and cemented with 175 sac and circulated to surface. 100' 24 hrs. Production Casing 5-1/2" OD 140' J-55 casing to be set through the lowest producing zone. Use centralizers and rotating type scratchers through the Gallup and cement with 100 sac 90-90 Miami "A" cement 4/25 gal. Drilling Core 90' of Lower Gallup Formation. Drilling logs planned. Logging Combination KB-Induction Log from TD to surface casing. Detail from TD to 100' above Upper Gallup through Pictured Cliffs & Ft. Leokaut sections. Microlog same as Detail KB. Run Gamma Ray in conjunction with perforating. Drilling Fluid Use Geolograph from 210' to TD. Drill Surveys At 90' intervals to 300'; thereafter, at 250' intervals. Depth Measurements GL of drill pipe at approximately 150' above the Hance and at TD. Samples Collect 10' samples from 200' above Ft. Leokaut to TD. Completion Program Whenever practicable, completion will be with rotary.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE BRITISH-AMERICAN OIL PRODUCING COMPANY  
Address P. O. Box 180  
Denver 1, Colorado  
By [Signature]  
Title District Superintendent

