

Form 3160-3  
(June 1990)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

## SUBMIT IN TRIPLICATE

## 1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Water Injection Well\* P&A

## 2. Name of Operator

Dugan Production Corp.

## 3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

## 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1880' FNL - 660' FWL  
Sec. 35, T26N, R13W, NMPMFORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

## 5. Lease Designation and Serial No.

SF 078155

## 6. If Indian, Allottee or Tribe Name

## 7. If Unit or CA, Agreement Designation

West Bisti Unit

## 8. Well Name and No.

West Bisti Unit 151

## 9. API Well No.

30-045-05626

## 10. Field and Pool, or Exploratory Area

\*Bisti Lower Gallup

## 11. County or Parish, State

San Juan, NM

## 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

## TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

## Plugged well as follows:

1. Set cast iron bridge plug on wireline at 4874'.
2. Spot 30 cu. ft. Class B cement on top of bridge plug. Gallup plug 4655' - 4874'.
3. Perforate Mesa Verde at 2600'.
4. Spot 77 cu. ft. Class B cement with 2% CaCl<sub>2</sub> at 2625'. Displace cement to 2155'. No flow back. Mesa Verde plug 2155' - 2625'.
5. Perforate Pictured Cliffs at 1341'.
6. Spot 89 cu. ft. Class B cement at 1343'. Displace cement to 761'. No flow back. Pictured Cliffs plug 761' - 1343'.
7. Perforate below surface casing at 264'.
8. Cement down 5 1/2" casing out bradenhead to surface with 138 cu. ft. Class B cement with 4% CaCl<sub>2</sub>.

Job complete 5-27-93.

Signatures to give plan of this well. Including surface location of well. Surface preparation to be completed.

## 14. I hereby certify that the foregoing is true and correct

Signed John Alexander  
(This space for Federal or State office use)Title Operations ManagerDate 6/1/93

Approved by \_\_\_\_\_

Conditions of approval, if any: \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOC

DISTRICT MANAGER

RECEIVED  
BLM  
93 JUN 14 AM 11:04  
070 FARMINGTON, NM