


(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee Navajo Tribal

Lease No. 14-20-0603-6370



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 21, 1961

Navajo Tract 27

Well No. 1 is located 1980 ft. from N line and 660 ft. from E line of sec. 32

SE NE Sec. 32

(¼ Sec. and Sec. No.)

26N

(Twp.)

15W

(Range)

N.M.P.M.

(Meridian)

Wildcat

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the ~~ground~~ <sup>ground</sup> floor above sea level is 5555 ft.  
~~is elevation 5586 ft.~~

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

SEE SUPPLEMENTAL SHEET ATTACHED



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Pure Oil Company

Address P. O. Box 265

Moab, Utah

Alpine 3-3581

By J. L. Strong

Title District Chief Clerk

SUNDRY NOTICES AND REPORTS ON WELLS

Navajo Tract 27 Well No. 1

September 21, 1961  
Notice of Intention to Abandon Well

10,420 TD by Driller  
10,417 TD by Schaumberger

Drilling completed at 7:30 a.m. 9-19-61. Ran electric logs to TD.

Propose to plug and abandon well as follows:

10,050 - 10,250 - 200' - 100 sax Trinity Inferno with HRL<sub>4</sub> retarding agent  
9,000 - 9,100 - 100' - 50 sax Trinity Inferno with HRL<sub>4</sub> retarding agent  
7,950 - 8,050 - 100' - 50 sax Trinity Inferno with HRL<sub>4</sub> retarding agent  
7,350 - 7,450 - 100' - 50 sax Trinity Inferno with HRL<sub>4</sub> retarding agent  
6,050 - 6,150 - 100' - 50 sax Trinity Inferno with HRL<sub>4</sub> retarding agent

Anticipate pulling 5500' of 9-5/8" OD casing from well. After pulling casing it is proposed to put cement plugs as follows:

5,400 - 5,500 - 100' - 100 sax of 50 Neat and 50 Pozmix with 2% gel  
4,900 - 5,000 - 100' - 100 sax of 50 Neat and 50 Pozmix with 2% gel  
4,100 - 4,200 - 100' - 100 sax of 50 Neat and 50 Pozmix with 2% gel  
3,900 - 4,000 - 100' - 100 sax of 50 Neat and 50 Pozmix with 2% gel  
Top of conductor pipe - 5 sax of cement.

Will install dry hole marker in accordance with U. S. G. S. regulations.

Verbal approval obtained from Mr. P. T. McGrath, USGS, Farmington, New Mexico

