

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Approval expires 12-31-55.

Indian Agency Window Rock
Navajo
Allottee No. 6088
Lease No. 24-20-603-777

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sandfracs

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 4th, 1956


Well No. 1 is located 1000 ft. from N line and 1745 ft. from E line of sec. 31
NE/4 NW/4 Sec. 31 24N 3W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Ballard San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6313 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4-17-56 TO 1954: Flowing 61 MCF/day. Sandfraced from 1944: to 1954: with 17,280 gallons salt water and 28,050 gal sand, flushed with 1,950 gallons salt water. Maximum treating pressure 1100#, minimum 1100#, injection rate 19.4 bbls. per minute. After treatment flowing 242 MCF/day and 4 gallons water per hour.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company HANSON-WORTH
Address 405 1/2 West Broadway
Farmington, New Mexico

By [Signature]
Title Field Superintendent

Form 9-331b
(April 1952)

(SUBMIT IN TRIPLICATE)

Indian Agency Window Rock
Navajo
Allottee Na-0000
Lease No. 14-20-603-777UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Sandfract</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 is located 1000 ft. from [N] line and 1705 ft. from [E] line of sec. 31
NE 1/4 NE 1/4 Sec. 31 26N 3W R.M.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Ballard San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6313 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4-17-56 TD 1994'. Flowing 61 MCF/day. Sandfractured from 1944' to 1994' with 17,300 gallons salt water and 20,050' sand, flushed with 1,950 gallons salt water. Maximum treating pressure 1100', minimum 1100', injection rate 19.4 bbls. per minute. After treatment flowing 61 MCF/day and 4 gallons water per hour.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BRUNNEN-MONTIN
 Address 405 1/2 West Broadway
Farmington, New Mexico

By [Signature]
 Title Field Superintendent

