

5 BLM 1 File 1 WBU wlos

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

APR 13 AM 9:45

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078156

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 145

9. API Well No.

30-045-05640

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

RECEIVED
APR 18 1994

OIL CON. DIV.
DIST. 3

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL - 660' FEL
Sec. 34, T26N, R13W, NMPM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plan to plug well as follows:

1. Set cast iron bridge plug at Gallup top (4865') and spot 50' Class B cement on top.
2. Perforate below Mesa Verde top (2014') and spot 100' plug inside and outside casing with Class B cement.
3. Perforate below Pictured Cliffs top (1274') and spot Class B + 4% gel cement inside and outside casing to cover Fruitland top at 1050'.
4. Perforate 50' below surface casing (214') and cement to surface with Class B + 4% gel cement.

All plugs will be spotted with fresh water as previously allowed within this unit.

Class B: 1.18 cu. ft./sk; 15.6 lb./gal.

Class B + 4% gel: 1.55 cu. ft./sk; 14.1 lb./gal.

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Signed John Alexander

Title operations mgr.

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

NMOCD

APPROVED

Date 4-13-94

APR 13 1994

DISTRICT MANAGER

IN REPLY REFER TO:
(07337)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT
FARMINGTON DISTRICT OFFICE
1235 La Plata Highway
Farmington, New Mexico 87401

Attachment to Notice of

Re: Permanent Abandonment

Intention to Abandon

Well: 145 West Bisti
Unit

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Leases."
2. Mike Flaniken with the Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
3. The following modifications to your plugging program are to be made (when applicable):

1.) Perforate @ 325' and circulate cement
to the surface. (bottom of Ojo Alamo @ 275')

Office Hours: 7:45 a.m. to 4:30 p.m.