


FROM—	TO—	TOTAL FEET	FORMATION
0	1190	1190	Tan to gry cr-grn ss interbedded w/gry sh.
1190	1389	199	Qjo Alamo ss. White cr-grn s.
1389	1837	448	Kirtland form. Gry sh interbedded w/tight gry fine-grn ss.
1837	2073	236	Fruitland form. Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.
2073	2180	107	Pictured Cliffs form. Gry, fine-grn, tight, varicolored soft ss.

RECEIVED

U. S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



11-24-57
Total depth 2180'.
P & A in the following manner:
Cement plug from 1950 to 2180' w/70 sacks cement.
Cement plug from 1200-1450 w/75 sacks cement.
Cement plug from 100 to 200' w/30 sacks cement.
Cement plug from 90' to surface w/50 sacks cement.
Set 4' x 4" pipe as permanent marker.

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

HISTORY OF OIL OR GAS WELL