Form 3160-5 (June 1990)

Jim Walker, Navajo EPA (Shiprock)
UNITED STATES

DEPARTMENT OF THE INTERIOR

**BUREAU OF LAND MANAGEMENT** 

PORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 Lesse Designation and Serial No.

SF 078091

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottoe or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas X Only Water Injection Well #		West Bisti Unit
2. Name of Operator		West Bisti Unit 133
3. Address and Telephone No.		9. API Well No. 30-045-05668
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area *Bisti Lower Gallup
		II. County or Purish, State San Juan, NM
2. CHECK APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intest()	Abandonment Recompletion	Change of Plans New Construction
Subsequent Related APR - 3 19		Non-Routine Fracturing Water Shut-Off
Final Abandonary Netter (CO)		Conversion to Injection
DIST. 3	- simula play procedure	Dispose Water (Mate: Report sends of multiple completion on Wall Completion or Recognition Report and Los form )

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zonce pertinent to this work.)\*

Upon pulling the injection tubing from this well, it was found to have a fish in the hole at 3855'. Reports from previous operator indicated that a fish had been left in the hole which they had been unable to recover. Verbal approval was received from Errol Becher (BLM) on 3/24/95 to amend the plugging procedure.

A cement retainer will be set at 3850' and 150 cu. ft. Class B + 4% gel will be pumped below the retainer. This will be the Gallup plug. All other plugs will remain unchanged.

On 3/27/95 the cement retainer was set at 3850'. After pumping 4 bbl. water, communication was established around the retainer. Received verbal approval from Steve Mason to pump adequate cement around the retainer to cover 200' of 7-7/8" hole.

4. I hereby certify that the foregoing is true and correct Signed John Alexander	TideOperations Manager	Date 3/27/95
(This space for Federal or State office use)  Approved by Conditions of approval, if any:	Tide	Dete

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side

LEDISTET MANIACED