Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE OCCUPANTMENT OF THE INTERIOR (Other instructions on reverse side) **GEOLOGICAL SURVEY**

Form approved.

14-20-0603-010և

instructions	οn	re-	l					o. 42-K	
de)			5.	LEASE	DESIG	NATION	AND	SERIAL	NO
				٦ J.	20	0/0	2	Cant	1

SUNDRY NOTICES AND REPORTS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
(Do not use this form for proposals to drill or to deepen or plug	hack to a different recornely		
Use APPLICATION FOR PERMIT—" for such	proposals.)	Navajo	
оп. ГУ) gas	7. UNIT AGREEMENT NAME		
WELL A WELL OTHER			
. NAME OF OPERATOR	8. FARM OR LEASE NAME		
TEXACO Inc. Prod. Dept. Rocky Mtn.	Navajo Tribe "AL"		
		9. WELL NO.	
P. O. Box 810 Farmington, New Mex.	1CO 8/401	3	
See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT	
	1.0	ocito Dome, Pennsylvania	
		SURVEY OR AREA	
1970' from south line and 2130' from	om west line	28_26N_18W MYPM	
4. PERMIT NO. 15. ELEVATIONS (Show whether D	28-26N-18W, NN.PM. 12. COUNTY OR PARISH 13. STATE		
		San Juan New Lexico	
Check Appropriate Box To Indicate 1	Natura of Natice Person of		
NOTICE OF INTENTION TO:	i .		
ACTION OF INTENTION TO.	SUBS	EQUENT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE REPAIR WELL CHANGE PLANS	SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL CHANGE PLANS (Other)		to salt water DisX	
	Completion or Recor	obletion Report and Log form	
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertiner proposed work. If well is directionally drilled, give subsurface locs nent to this work.)* 	tions and measured and true vert	ical depths for all markers and zones perti-	
retainer set at 3800, was unable to indicated cement top at 3710. It squeezed with 850 sacks regular of 3772, NOC 20 hr. Liquid circular annulus. Drilled plugs and cement to 6345 with 4 jets per foot. A with 3000 gallens 28% HCL. Ran 6 tubing and set lok-set packer at annulus. Well ready for injection Telephone approval obtained from	Perforated 4 hole cement through relation during job to 6374'. Perfacidized 6313-16' 6235' of 2 3/6' 0 6251' with inhibon service 1-26-1	s at 3050' and tainer set at op 43"-8 5/8" orated 6334' and 0334-45'. D plastic lined ited water in 973.	
		DIST. 3	
I hereby certify that the foregoing is true and correct			
$I_{1}I_{2}I_{3}I_{4}I_{4}I_{4}I_{4}I_{4}I_{4}I_{4}I_{4$	ald Wanaman	2 02 2-22	
SIGNED W. F. W. CLOW TITLE F'I	eld Foreman	DATE 1-29-1973	
(This space for Federal or State office use)			
APPROVED BYTITLE			
CONDITIONS OF APPROVAL, IF ANY:		DATE	