

A 10x10 grid with an 'X' in the 7th column and 3rd row from the bottom.

Santa Fe, New Mexico

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Delhi-Taylor

.....
(Company or Operator)

(Leave)

Well No. 1-A, in NE $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 28, T. 26 N, R. 11 W, NMPM.
Wildcat Pool San Juan County

Well is 2310 feet from South line and 660 feet from East line.

of Section 28 If State Land the Oil and Gas Lease No. is Fee- S. R. Drolet

Drilling Commenced October 12, 1957 Drilling was Completed October 23, 1957

Name of Drilling Contractor.....**Summitt Drilling Company**.....

Address Farmington, New Mexico

Elevation above sea level at Top of Tubing Head 6187' The information given is to be kept confidential until
 _____, 19____.

No. 1, from 4900 to 4955	No. 4, from 5127 to 5200
No. 2, from 5022 to 5055	No. 5, from to
No. 3, from 5083 to 5120	No. 6, from to

Include data on rate of water inflow and elevation to which water rose in hole.


No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from.....to.....feet.

U.S. GEOLOGICAL SURVEY
WATER RESOURCES DIVISION
WASHINGTON, D. C. 20006
OCT 30 1965
CON
DIS



SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4	32.75	New	170'	Howco			Surface
7 5/8	26.40	New	4074'	Baker			Intermediate
7 5/8	26.40	New	1321'		1332'		Abandon

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	10 3/4	173'	150	Circulated		
9 7/8	7 5/8	4085'	250	Circulated		

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

This well was plugged & abandoned in the following manner:

1. Retainer set at 3895' & 100 sks. reg. cement below retainer.
2. Cut 7 5/8" csg. at 1332' & pulled 1321'.
3. Set cement plugs from 1246' to 1376' with 50 sks. rg. cement, & from 57' to surface with 25 sks. reg. cement & 2% CaCl₂.
4. Set 4 1/2" D.P. marker 4' above surface.

...Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing....., 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....	327	T. Kirtland-Fruitland.....	480		
T. Salt.....	T. Silurian.....	T. Farmington.....		T. Pictured Cliffs.....	1347		
B. Salt.....	T. Montoya.....	T. Mesa M. Verde.....	2240	T. Point Lookout.....	3855		
T. Yates.....	T. Simpson.....	T. Mancos.....	4049	T. Dakota.....			
T. 7 Rivers.....	T. McKee.....	T. Morrison.....		T. Penn.....			
T. Queen.....	T. Ellenburger.....	T. Gallup.....	4900				
T. Grayburg.....	T. Gr. Wash.....						
T. San Andres.....	T. Granite.....						
T. Glorieta.....	T.						
T. Drinkard.....	T.						
T. Tubbs.....	T.						
T. Abo.....	T.						
T. Penn.....	T.						
T. Miss.....	T.						

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	327	327					
327	480	153	Ojo Alamo -ss. White cr-grn s.				
480	858	378	Kirtland - Gry sh interbedded w/tight gry fine-grn ss.				
858	1347	489	Fruitland - Gry carb sh, scattered coals, coals & gry, tight, fine				
1347	2240	893	Pictured Cliffs - Gry fine-grn tight, varicolored soft ss.				
2240	3855	1615	Mesa Verde - Gry, fine-grn, dense sil ss., carb sh & coal.				
3855	4049	194	Point Lookout - Gry very fine sil ss w/frequent sh breaks.				
4049	4900	851	Mancos - Gry carb sh.				
4900	5260	360	Gallup - Lt gry to brn calc carb micac glauco very fine gry ss w/irreg. interbed sh.				

OIL CONSERVATION COMMISSION	
AZTEC DISTRICT OFFICE	
No. Copies Received	6
DISTRIBUTION	
Operator	
Santa Fe	
Production Office	
State Land Office	
J. S. G. S.	
ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED	
I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.	

October 29, 1957 (Date)

Company or Operator El Paso Nat. Gas Prod. Co. Address P.O. Box 1565; Farmington, N. Mexico
Name William K. Hargner Position or Title Petroleum Engineer