

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. 078630
Unit Foster-Riddle

(Orig. Sec.) U. W. LONG

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
MAY 28 1956
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

May 25th, 1956

Well No. 2 is located 2230 ft. from N line and 1660 ft. from E line of sec. 25

SW 1/4 NE 1/4 Sec. 25 26N 8W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Ballard
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6387 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

2-15-56 TD 2286' RKB. Set 15 joints 478' of 5-1/2" OD 15.5# J-55 casing and 54 joints 1733' of 5-1/2" OD 14# J-55 casing at 2194' with 100 sacks cement.

3-16-56 Pressured up on casing to 1000#. No pressure decrease in one hour.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company BENSON-MONTIN-GREER DRILLING CORP.

Address 405 1/2 West Broadway

Farmington, New Mexico



Title Vice-President

