

JUN 1 1956

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. 078630
Unit Foster-Riddle(Orig. Sub. No. 100)
GEOLOGICAL SURVEYUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR REPAIRING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sand-Oil Treatment

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 25th, 1956

Well No. 2 is located 2230 ft. from N line and 1660 ft. from E line of sec. 25SW 1/4 NE 1/4 Sec. 25
(1/4 Sec. and Sec. No.)26N
(Twp.)8W
(Range)N.M.P.M.
(Meridian)Ballard
(Field)San Juan
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6387 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3-18-56 TD 2286'. Flowing 98 MCF/day. Sand-oil treated from 2194' to 2286' with 7,625 gallons diesel oil and 15,000# sand, flushed with 2,435 gallons diesel oil. Breakdown pressure 1650#, treating pressure; 1100#, final pressure 1100#, injection rate 33.8 barrels per minute under pressure. After treatment flowing 167 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company BENSON-MONTIN-GREER DRILLING CORP.Address 405 1/2 West BroadwayFarmington, New MexicoBy Albert H. Greer
Title Vice-President

