

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED
MAY 23 1994

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL - 660' FWL
Sec. 27, T26N, R13W, NMPMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078091

6. If Indian, Alibon or Tribe Name

7. If Unit or CA, Agroceptual Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 126

9. API Well No.

30-045-05686

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug well as follows:

1. Set cast iron bridge plug at Gallup top (4900') and spot 50' Class B cement plug to top of plug.
2. Spot 100' Class B cement plug across Mesa Verde top (2024') inside casing. Mesa Verde top was squeezed outside casing with 413 cu. ft. cement in 1983, through a hole found at 2281.
3. Perforate 50' below Pictured Cliffs top (1343') and spot Class B + 4% gel plug to cover Fruitland top (1112').
4. Perforate 50' below surface casing (214') and circulate Class B + 4% gel to surface.

Water will be used to spot all plugs as permitted on other wells in this area.

Class B = 15.6 lb./gal.; 1.18 cu. ft./sk.

Class B + 4% gel = 14.1 lb./gal.; 1.55 cu. ft./sk.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander
(This space for Federal or State office use)Title Operations ManagerDate 5/10/94Approved by _____
Conditions of approval, if any:

Title _____

Date _____

AS AMENDED

MAY 17 1994