

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ GAS ☐ WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Elliott Oil Company	8. FARM OR LEASE NAME CM&W
3. ADDRESS OF OPERATOR P. O. Box 1355 Roswell, New Mexico 88201	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit F-SE 1/4 NW 1/4 Sec. 30, T26N-R13W (1980' from North & 2520' from West lines of Section)	10. FIELD AND POOL, OR WILDCAT West Blati
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30-T26N-R13W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6512 Gr.	12. COUNTY OR PARISH San Juan
	13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☒
(Other)	☐		☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged & abandoned as follows:

1. Pumped cement plug from PBTD. 5359' to 5100'.
2. Filled CSNG. w/ heavy mud from 5100' to 1540'.
3. Perforated 4 holes at 1540' and squeezed 35 sacks cement into formation leaving 50' cement in casing.
4. Filled hole with heavy mud from 1490' to 450'.
5. Perforated 4 holes at 450' and squeezed 35 SKS cement into OJO Alamo formation, leaving 50' cement in CSNG.
6. Pumped 10 SKS cement in 5 1/2" CSNG. from 150' to 60'.
7. Pumped 40 SKS. cement down surface CSNG.
8. Put cement plug at surface in 5 1/2" production CSNG. and 10 3/4" surface CSNG.
9. Cut off surface CSNG and 5 1/2" CSNG. 4' below grnd. level.
10. Welded steel plate across top of surface casing.
11. Cleaned location.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

RECEIVED

NOV 13 1978

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 10 1979

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

G.P.O. : 1973- 780-622 /VIII- 148

