For (1	reb. 1	-881 a 951)	•

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	-San	ta.	P•
Louse No.	S P	07	937
Unit		حملا	Davis

	지수는 그는	N 1 - *
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL		
TOTICE OF INTENTION TO ADMITTON WELL.	Report of 3rd Ferforetion Report of 3rd Sand-Fracing	
	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)	<u>).,</u> 19 57
F. L. Davis [ell No. 1 is located 990 ft. from [/4-NE/4-ME/4 Sec. 26 268 (Twp.)	m Nome Falling of sec	· 26
Ideat (Dakota) Ser	or Subdivision) (State or Territory)	
ate names of and expected depths to objective sands; show si	AILS OF WORK izes, weights, and lengths of proposed casings; indicate mudding jother important proposed work)	obs, cement-
	4 Lane Wells Type "E" bullets per ft at 6108' with Halliburton HM packer s -38', down 22" tubing, with 6000% 40-x. Th 5300%, Min. Th 5000%, Inj. retent-down pressure 2400%.	
eced 5gm casing perforations 6130- 100 gal. lease oill BDP 5000s, New	-38' down 22" tubing with 6000% 40- x. TP 5300%, Min. TP 5000%, Inj. rete	
eced 5gm casing perforations 6130- 100 gal. lease oill BDP 5000s, New	-38', down 2'" tubing, with 6000% 40- x. TP 5300%, Min. TP 5000%, Inj. rete at-down pressure 2400%.	
raced 5gm casing perforations 6130- CO gal. lease dill BDP 5000%, Man ptal time of treatment 27 min. Sho	38' down 2'" tubing with 6000 40- x. TP 5300, Min. TP 5000, Inj. rete ut-down pressure 2400.	
reced 5gm casing perforations 6130-100 gal. lease cill BDF 5000s, Manual time of treatment 27 min. Shu	38', down 2'" tubing with 6000 40- x. TP 5360', Min. TP 5000', Inj. rete at-down pressure 2400'.	

Title District Superintendent