STATE OF NEW MEXICO



SECRETARY

ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE

1000 RIO BRAZOS ROAD AZTEC, NEW MEXICO 87410 (505) 334-6178

November 6, 1981

Mr. Ron Rovenko Getty Oil Company P. O. Box 3360 Casper, WY 82602

Re: Plugging Programs for P. L. Davis #1, A-26-26N-11W and P. L. Davis #2, L-26-26N-11W

Dear Mr. Rovenko:

The plugging program for the P. L. Davis #1 is as follows:

PB to 5970
5700 to 5100
2500 to 2400
Perforate & Squeeze (perforate at bottom of plug)
1750 to 1600
Perforate & Squeeze (perforate at bottom of plug)
1150 to 1050
Perforate & Squeeze (perforate at bottom of plug)
750 to 650
Perforate & Squeeze (perforate at bottom of plug)
320 to 220
10 sks at top with dry hole marker

to bits no out when any money imaginer

The plugging program for the P. L. Davis #2 is as follows:

If I can be of any further service, please contact this office.

Yours truly,

Jeff A. Edmister

Geologist/Field Representative

JAE:gc

cc: Operator file
/Well files
Reading file