

	X	
	29	

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **078091**
Unit **Gov't. Dearthit**

MAY 20 1958

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	X	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Dearthit May 15, 1958
Well No. **"B" #18** is located **6** ft. from **[N]** line and **6** ft. from **[E]** line of sec. **29**
C NE NW Section 29 **26N** **13W** **New Mexico P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Bisti-Gallup **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6572** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

PROGRAM: To drill and test subject well to the Gallup S.S. **Surface Casing:** 9-5/8" OD, ASW casing to be set approx. 200' KB and cemented with 175 sax and circulated to surface. WOC 24 hours. **Production Casing:** 5-1/2" OD 14# J-55 casing to be set through the lowest producing zone. Use centralizers and rotating type scratchers thru the Gallup and cement with 100 sax 50-50 Diamix "A" cement w/2% Gel. No coring planned. **Testing:** If content of sands based on electric log is questionable, DST's will be taken. **Logging:** Combination ES-Induction Log from TD to surface csg. Detail thru Pictured Cliffs, Ft. Lookout, Gallup. Microlog same as Detail ES. Gamma Ray in conjunction with perforating. **Drilling Time:** Use Geolograph from 210' TD, w/perf. **Drift Surveys:** At 50' intervals to 300'; thereafter at 250' intervals. **Depth Measurements:** SLM of drill pipe at approx. 150' above the Mancos, prior to coring, DST & at TD. **Sampling:** Collect 10' samples from 1300' to TD. **Completion Program:** Whenever practicable, completion will be with retary.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **THE BRITISH-AMERICAN OIL PRODUCING COMPANY**

Address **P. O. Box 180**

Denver, Colorado

By _____
Title **District Superintendent**