

Form 3160-3
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL - 1980' FWL
Sec. 29, T26N, R13W, NMPM

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078091

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 121

9. API Well No.

30-045-05714

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged to abandon as follows:

1. Tag cement plug @ 5140' with tubing.
2. Isolate hole in casing at 315'.
3. Perforate 5½" casing at 2962' for Mesa Verde plug.
4. Spot 40 cu. ft. Class B cement across hole and displace 18 cu. ft. outside casing. Mesa Verde plug 2800'-2962'.
5. Perforate at 1812' for Pictured Cliffs - Fruitland plug.
6. Pump 145 cu. ft. Class B cement, leaving 46 cu. ft. inside 5½" casing. Pictured Cliffs - Fruitland plug 1478'-1812'.
7. Perforate at 518' for plug below base of Ojo Alamo.
8. Pump 47 cu. ft. Class B with 4% gel cement. Displaced to 360'. Ojo Alamo base plug 360'-518'.
9. Pump 120 cu. ft. Class B with 4% gel, followed by 24 cu. ft. Class B cement through hole in 5½" casing at 315'. Circulated cement to surface. Ojo Alamo top - surface plug 0'-315'.
10. Job complete 4-27-93. Operations observed by Ron Snow, BLM.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Operations Manager

Date

4/29/93

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

DISTRICT MANAGER