


(SUBMIT IN TRIPLICATE)

Indian Agency Tribal Lands



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Navajo

Lease No. 14-20-60-2076

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3, 1958

Well No. Burnham 14-24 is located 560 ft. from RS line and 4620 ft. from E line of sec. 24

SW 24 26 N 15 W BURN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat - Burnham San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the Kelly Pushing 5013 ft. above sea level is

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 11-21-58

11-21-58 Ran and cemented 4 joints (13-1) 3 5/8", 28#, J-55 casing at 142' with 12 sacks, 190 cu. ft. Portland cement, treated with 2% calcium chloride, approx. surface temperature 25° ±, formation temperature 75° P ±. Estimate strength of cement 1000 psi. Flanged up and waited on cement. Pressure tested casing and BOP with 700 psi, OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address 705 Municipal Drive
Farmington, New Mexico

Original signed by
B. W. SHEPARD

By B. W. Shepard
Title exploitation engineer